

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

LIFE-SAVING IMMERSION SUIT

Immersion Suit

The products meet the requirements of the international convention for the safety of life at sea and rescue equipment (LSA)rules. Thermal protectiveness:after immersing in the 0°C-+2°C still water for 6h, the body temperat...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Life-Saving Immersion Suit
Standard	CB
Material	Outside material :Waterproof Beryline oxford textile Inside material :Fo...
Weight / Size	Type II Immersion suits Main material :CR neoprene sponge (thickness:5m...
Certificate	CCS / EC

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Life-Saving Immersion Suit	Model / SKU	Immersion-Suit
Standard	CB	Material	Outside material :Waterproof Beryline oxford textile Inside material :Foamed polyethylene ,Aluminum plate film.
Weight / Size	Type II I mmersion suits Main material :CR neoprene sponge (thickness:5mm) Type Specification Stature Package dimension Type I XL Above 1.8m 56x34x32cm L 1.65-1.8m 56x34x51cm M Below 1.65m 56x34x74cm Type-II XL Above 1.8m 58x23x36cm L 1.65-1.8m 58x42x36cm M Below 1.65m	Certificate	CCS / EC
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Immersion Suit:	■ Type I immersion suits
	■ Type II I mmersion suits	

China Immersion Suit:

The products meet the requirements of the international convention for the safety of life at sea and rescue equipment (LSA)rules.Thermal protectiveness:after immersing in the0°C-+2°Cstill water for 6h,the body temperature shall not fall2°Cbelow the normal level.

Type I immersion suits

Outside material :Waterproof Beryline oxford textile

Inside material :Foamed polyethylene ,Aluminum plate film.

Type II I mmersion suits

Main material :CR neoprene sponge (thickness:5mm)

Type	Specification	Stature	Package dimension
Type I	XL	Above 1.8m	56x34x32cm
	L	1.65-1.8m	56x34x51cm
	M	Below 1.65m	56x34x74cm



Type-II	XL	Above 1.8m	58x23x36cm
	L	1.65-1.8m	58x42x36cm
	M	Below 1.65m	