

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

LIFE BOAT & RESCUE BOAT

Inflatable Fender Rigid Fast Rescue Boat

ISO9001 Supplier

Class Certificate

Export Supply

It is made of glass fiber reinforced plastic material. Inflatable fender is surrendered the hull, which could provide enough buoyant for the rescue boat. Both sides of the rescue boat are equipped with stainless steel h...



Key Highlights

Category	Life boat & Rescue Boat
Standard	EN
Material	Glass fiber reinforced plastic material
Weight / Size	Type JBB65Q With outboard engine JBB65Q With inboard engine JBB78Q ...
Certificate	CCS, BV, DNV, ABS, GL, LR, RINA, NK

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Life boat & Rescue Boat	Model / SKU	Inflatable-Fender-Rigid-Fast-Rescue-Boat
Standard	EN	Material	Glass fiber reinforced plastic material
Weight / Size	Type JBB65Q With outboard engine JBB65Q With inboard engine JBB78Q With inboard engine Main dimension (M) 6.8*2.45*0.9 6.8*2.45*0.9 7.88*2.9*0.78 Capacity P(82.5Kg/p) 9 9 15 Light Weight 1450 kg 1750kg 2265kg Fully loaded Weight 2192.5kg 2492.5kg 3502.5kg Fender Hypalon tube Hypalon tube Hypalon tube	Surface	1.Fit the off-load &stainlessness release mechanism with the safety pin 2.The walk around deck has an anti-slip surface 3.Running time of rescue boat when full-loaded and full-speed is more than 4h.
Certificate	CCS, BV, DNV, ABS, GL, LR, RINA, NK	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ China Inflatable Fender Rigid Fast Rescue Boat: ■ Available Model: 	<ul style="list-style-type: none"> ■ Specification:
-----------------	---	--

China Inflatable Fender Rigid Fast Rescue Boat:


It is made of glass fiber reinforced plastic material. Inflatable fender is surrendered the hull, which could provide enough buoyant for the rescue boat. Both sides of the rescue boat are equipped with stainless steel handrails for occupant coming and down. The rescue boat is strictly in compliance with the amendments to the SOLAS, 1974, MSC218. (82), MSC226. (82), MSC272. (85) and MSC274. (85).

Specification:

1. Fit the off-load &stainlessness release mechanism with the safety pin
2. The walk around deck has an anti-slip surface
3. Running time of rescue boat when full-loaded and full-speed is more than 4h.
6. Certificate: CCS, BV, DNV, ABS, GL, LR, RINA, NK

Available Model:

Type	JBB65Q With outboard engine	JBB65Q With inboard engine	JBB78Q With inboard engine
------	--------------------------------	-------------------------------	-------------------------------



Main dimension (M)	6.8*2.45*0.9	6.8*2.45*0.9	7.88*2.9*0.78
Capacity P(82.5Kg/p)	9	9	15
Light Weight	1450 kg	1750kg	2265kg
Fully loaded Weight	2192.5kg	2492.5kg	3502.5kg
Fender	Hypalon tube	Hypalon tube	Hypalon tube