


MARINE NAVIGATION EQUIPMENT

JB-5000 AIS SART

- ISO9001 Supplier
- Class Certificate
- Export Supply

1. Frequency range : CH87B(161.975 MHz)/CH88B(162.025 MHz); 2. Frequency error: $\leq \pm 0.5\text{KHz}$; 3. Radiated Power : $\geq 1\text{W}$; 4. Modulation spectrum :the frequency deviation from the carrier center frequency $\pm 10\text{KHz}$,the modulatio...



Key Highlights	
Category	Marine Navigation Equipment
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	

Technical Specifications			
Category	Marine Navigation Equipment	Model / SKU	JB-5000-AIS-SART
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China JB-5000 AIS SART:

1. Frequency range : CH87B(161.975 MHz)/CH88B(162.025 MHz);
2. Frequency error: $\leq \pm 0.5\text{KHz}$;
3. Radiated Power : $\geq 1\text{W}$;
4. Modulation spectrum :the frequency deviation from the carrier center frequency $\pm 10\text{KHz}$,the modulation sidebands $\leq -20\text{dBc}$;
- deviation from the carrier center frequency of $+25\text{KHz} \sim +62.5\text{KHz}$ and $-25\text{KHz} \sim -62.5\text{KHz}$,the device modulation sidebands $\leq -40\text{dBc}$;
5. Modulation: GMSK
6. Operation temperature: $-20^\circ\text{C} \sim +55^\circ\text{C}$
7. Compass safe distance: 60 cm
8. Battery: lithium cell

9. Operation life: 96 H
10. Storage time: 3 Years
11. Reference: IEC61097-14(2010); IEC-60945(2002)