MARINE CONSERVATION


JINBO Bridge Navigational Watch Alarm System

ISO9001 Supplier

Class Certificate

Export Supply

Description DJC-N Bridge Navigational Watch Alarm System (BNWAS) has been developed and manufactured by Shanghai DONJUN automation equipment co., ltd. The system meets with the Marine Safety Committee resolutio...



Key Highlights

Category	Marine Conservation
Standard	DIN
Weight / Size	The system meets with the Marine Safety Committee resolution MSC.128 (75...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Conservation	**Model / SKU**	JINBO-Bridge-Navigational-Watch-Alarm-System
Standard	DIN	**Weight / Size**	The system meets with the Marine Safety Committee resolution MSC.128 (75) and MSC.282 (86) which requested July 1, 2011 or after the construction of more than 150 gross tonnage cargo ships and passenger ships irrespective of size are required to install the BNWAS system.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Description
- System parameters：

Description

DJC-N Bridge Navigational Watch Alarm System (BNWAS) has been developed and manufactured by Shanghai DONJUN automation equipment co., ltd. The system meets with the Marine Safety Committee resolution MSC.128 (75) and MSC.282 (86) which requested July 1, 2011 or after the construction of more than 150 gross tonnage cargo ships and passenger ships irrespective of size are required to install the BNWAS system. The system monitors the awareness of the officer of the watch and automatically alerts the Master or another qualified officer if any reason the watch officer becomes incapable of performing the watch duties. The system is achieved by a series of indications and alarms to alert first watch officer and, if he is not responding, then to alert the Master or another qualified officer to avoiding operational navigational accidents. The system also provide with a emergency calling function for watch officer for immediate assistance if required.

System parameters：

Working voltage：100-24VAC & DC24V Time precision：±0.75 Seconds
Power consumption：Max 45w

Input /Output：11 Circuit+ Extension/20 Circuit+ Extension/
System insulating Performance: ≧10MΩ
Working environment: -25℃ ~ 55℃
System voltage performance: ≧500V/min
Alert level: Pre-alarm、First stage alarm、Second stage alarm、third stage alarm Alarm range：The largest to the whole ship alarm

