

**TURNBUCKLE**

# JIS F 3403 Rigging Screws

Drop forged frame with a solid thimble and bolt ends, Rigging Screws used for standing rigging of ships' mast and post. Please specify the diameter of wire rope to be used when ording, also please specify galvanize...

- ISO9001 Supplier
- Class Certificate
- Export Supply



## Key Highlights

<b>Category</b>	Turnbuckle
<b>Standard</b>	JIS
<b>Material</b>	Rigging Screws Construction and Material Specification Nominal Size Dia.
<b>Weight / Size</b>	Rigging Screws Construction and Material Specification Nominal Size Dia.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

<b>Category</b>	Turnbuckle	<b>Model / SKU</b>	JIS-F-3403-Rigging-Screws
<b>Standard</b>	JIS	<b>Material</b>	Rigging Screws Construction and Material Specification Nominal Size Dia.
<b>Weight / Size</b>	Rigging Screws Construction and Material Specification Nominal Size Dia.	<b>Surface</b>	galvanized
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China JIS F 3403 Rigging Screws: Specification</li> <li>■ Rigging Screws Construction and Material</li> </ul>
-----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------



## China JIS F 3403 Rigging Screws:

Drop forged frame with a solid thimble and bolt ends, Rigging Screws used for standing rigging of ships' mast and post.

Please specify the diameter of wire rope to be used when ordering, also please specify galvanized or ungalvanized.

## Rigging Screws Construction and Material



## Specification

Nominal Size	Dia. Of Wire Rope	Nomial Size of Wire Socket	SWL(Ton)	Weight(Kg)
14	14	2.1	5.97	
16	16	16	2.6	8.58
18	18	18	3.3	11.6
22	20-22.4	20-22	5.5	14.8
24	24	24	5.9	19.4
26	25	26	6.9	23.9
30	28-30	28-30	9.2	30.2
32	32	32	10.5	43.2
36	36	36	13	51.1
38	38	38	14.5	59.9
40	40	40	16.5	70.7
42	42.5	42	18.5	93.5
45	45	45	21	105
48	47.5	48	23	117
50	50	50	25.5	124



