STERN TUBE SEAL

JQ/CS 49 Type Stern Tube seal

ISO9001 Supplier

Class Certificate

Export Supply

Product Application When inland water vessels have oil as their lubricating working medium and do not have a large stern shatf,this type of apparatuses is suggested to be chosen. Product Specification ...



Key Highlights

Category	Stern Tube Seal
Standard	EN
Weight / Size	Product Specification Model D A B C F H K N P S T n d n1 Weight (kg) Fro...
Certificate	BV, ABS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Stern Tube Seal	**Model / SKU**	JQ-CS-49-Type-Stern-Tube-seal
Standard	EN	**Weight / Size**	Product Specification Model D A B C F H K N P S T n d n1 Weight (kg) Front Back 130JQ/CS49 130 320 290 250 145 28 140 160 215 230 200 8 11 8 26 38 150JQ/CS49 150 345 310 270 165 28 145 180 235 250 220 8 11 8 29 42 170JQ/CS49 170 366 336 292 185 28 150 200 260 270 240 12 13 8 34 46 190JQ/CS49 190 390 360 320 205 28 160 220 290 295 260 12 13 8 40 53 210JQ/CS49 210 410 380 335 225 32 160 246 310 320 280 16 13 12 45 59 230JQ/CS49 230 445 410 370 245 32 170 266 350 340 300 16 15 12 53 66 250JQ/CS49 250 475 440 390 270 34 175 290 370 360 326 16 17 12 60 73 280JQ/CS49 280 505 470 420 300 34 180 320 400 390 356 16 17 12 68 82 320JQ/CS49 320 550 510 460 340 34 180 360 440 430 390 16 22 12 76 90 360JQ/CS49 360 590 550 500 380 36 180 405 480 470 430 16 22 12 84 98 For more details, please contact us.
Certificate	BV, ABS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Product Application
- Product Specification

Product Application

When inland water vessels have oil as their lubricating working medium and do not have a large stern shatf,this type of apparatuses is suggested to be chosen.

Product Specification



Model	D	A	B	C	F	H	K	N	P	S	T	n	d	n1	Weight (kg)	
															Front	Back
130JQ/CS49	130	320	290	250	145	28	140	160	215	230	200	8	11	8	26	38
150JQ/CS49	150	345	310	270	165	28	145	180	235	250	220	8	11	8	29	42
170JQ/CS49	170	366	336	292	185	28	150	200	260	270	240	12	13	8	34	46
190JQ/CS49	190	390	360	320	205	28	160	220	290	295	260	12	13	8	40	53
210JQ/CS49	210	410	380	335	225	32	160	246	310	320	280	16	13	12	45	59
230JQ/CS49	230	445	410	370	245	32	170	266	350	340	300	16	15	12	53	66
250JQ/CS49	250	475	440	390	270	34	175	290	370	360	326	16	17	12	60	73
280JQ/CS49	280	505	470	420	300	34	180	320	400	390	356	16	17	12	68	82
320JQ/CS49	320	550	510	460	340	34	180	360	440	430	390	16	22	12	76	90
360JQ/CS49	360	590	550	500	380	36	180	405	480	470	430	16	22	12	84	98

For more details, please contact us.