

GENERAL EMERGENCY ALARM SYSTEM

KG-3JK General Emergency Alarm Controller

ISO9001 Supplier

Class Certificate

Export Supply

KG-3JK General Emergency Alarm Controller Main power:AC220V±10% Emergency power: DC24V -25% +30% Alarm signal frequency: 1000±50Hz General emergency alarm time sequence: ...



Key Highlights

Category	General Emergency Alarm System
Standard	DIN
Weight / Size	KG-3JK General Emergency Alarm Controller Main power:AC220V±10% Emergenc...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS


We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.


Technical Specifications

Category	General Emergency Alarm System	Model / SKU	KG-3JK-General-Emergency-Alarm-Controller
Standard	DIN	Weight / Size	KG-3JK General Emergency Alarm Controller Main power:AC220V±10% Emergency power:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China KG-3JK General Emergency Alarm Controller:

KG-3JK General Emergency Alarm Controller





Main power: AC220V±10%

Emergency power: DC24V -25% +30%

Alarm signal frequency: 1000±50Hz

General emergency alarm time sequence:

7 short pulses followed by a long pulse. Resend it every two seconds

Fire alarm time sequence: continuous modulated long tone

Manual alarm time sequence: Output according to the switch on or off

Interface signal level between general emergency alarm controller and public address: -7 ±1dB

Interface resistance level between general emergency alarm controller and public address: 1k

Passive contact load(resistance): 8A/250VAC

KG-3JK Color: black (RAL9005)

IP class: IP20

Weight: 9.5Kg

Power: 10W