

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

LIFE RAFT

KHD Type Davit-Launched Inflatable Liferrafts

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: KHD type davit-launched inflatable liferafts are in accordance with 1996 Amendment to the International Convention for the Safety of Life at Sea, 1974, MSC.81 (70) , MSC.218(82), MSC.226(82)...



Key Highlights

Category	Life Raft
Standard	ISO
Weight / Size	Type KHD-12 KHD-15 KHD-16 KHD-20 KHD-25 Physical form rectangular octago...
Certificate	CCS,EC

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Life Raft	Model / SKU	KHD-Type-Davit-Launched-Inflatable-Liferrafts
Standard	ISO	Weight / Size	Type KHD-12 KHD-15 KHD-16 KHD-20 KHD-25 Physical form rectangular octagon decagon decagon decagon dodecagon Capacity 12 15 16 20 25 Length (mm) , ±1000 2990 3300 3430 3780 4180 Width (mm) , ±1000 2990 3300 3430 3780 4180 Height (mm) , ±50 1750 1850 1950 2100 2250 Pack Dia (mm) 695 700 700 790 790 Length (mm) 1285 1275 1275 1390 1390 Weight , kg ≤ 137 153 163 188 211
Certificate	CCS,EC	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ Product Description: ■ Available Model:
-----------------	--

Product Description:

KHD type davit-launched inflatable liferafts are in accordance with 1996 Amendment to the International Convention for the Safety of Life at Sea, 1974, MSC.81 (70) , MSC.218(82), MSC.226(82) and ISO 15738-2002. This product has been approved by CCS, EC (GL), ABS, LR and NK. It can be used in the ships engaged on international voyages.

inflatable davit-launch type, design for ships engaged in international voyage.

Available Model:

Type	KHD-12	KHD-15	KHD-16	KHD-20	KHD-25
Physical form	rectangular octagon	decagon	decagon	decagon	dodecagon
Capacity	12	15	16	20	25
Length (mm) , ±1000	2990	3300	3430	3780	4180
Width (mm) , ±1000	2990	3300	3430	3780	4180
Height (mm) , ±50	1750	1850	1950	2100	2250
Pack	Dia (mm)	695	700	700	790
	Length (mm)	1285	1275	1275	1390
Weight , kg ≤	137	153	163	188	211

