

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE BATTERYLESS TELEPHONE SYSTEM

KS/12KS/24KS-1J Batteryless Telephone

KS/12KS/24KS-1J Batteryless Telephone Ambient noise:≤120dB Ringing sound level: >85dB(A) Power supply: DC24V -25% +30% Color: black (RAL9005) IP class:IP44 Weight...

ISO9001 Supplier

Class Certificate

Export Supply



KS-1J

12KS-1J

24KS-1J

Key Highlights

Category	Marine Batteryless Telephone System
Standard	EN
Weight / Size	black (RAL9005) IP class:IP44 Weight:2.06/2.14/3.3Kg Power:1W Stuffing bo...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Batteryless Telephone System	Model / SKU	KS-12KS-24KS-1J-Batteryless-Telephone
Standard	EN	Weight / Size	black (RAL9005) IP class:IP44 Weight:2.06/2.14/3.3Kg Power:1W Stuffing box cable entrance hole size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China KS/12KS/24KS-1J Batteryless Telephone:

KS/12KS/24KS-1J Batteryless Telephone





Ambient noise: $\leq 120\text{dB}$

Ringing sound level: $> 85\text{dB(A)}$

Power supply: DC24V -25% +30%

Color: black (RAL9005)

IP class: IP44

Weight: 2.06/2.14/3.3Kg

Power: 1W

Stuffing box cable entrance hole size:

KS-1J : 1- $\Phi 14\text{mm}$; 1- $\Phi 18\text{mm}$;

12KS-1J: 1- $\Phi 14\text{mm}$; 1- $\Phi 25\text{mm}$;

24KS-1J: 1- $\Phi 14\text{mm}$; 1- $\Phi 38\text{mm}$