MEASUREMENT AND CONTROL DEVICE

LXZ Type Spiral Rotor Flowmeter

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: It is a latest volume type flow meter, it adopt one pair special dentiform spiral rotor. It features pulseless, low voice,high accuracy, high reliablity,large flow,high environmental suitabilit...



Key Highlights

Category	Measurement And Control Device
Standard	GB
Material	Nominal diameter" DN25 to 300mm Body material:
Certificate	CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Measurement And Control Device	**Model / SKU**	LXZ-Type-Spiral-Rotor-Flowmeter
Standard	GB	**Material**	Nominal diameter" DN25 to 300mm Body material:
Certificate	CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC.	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Product Description:
- Main Technical Specificatioin:

Product Description:

It is a latest volume type flow meter, it adopt one pair special dentiform spiral rotor. It features pulseless, low voice,high accuracy, high reliablity,large flow,high environmental suitability etc. It is mainly used for the commercial trade measurment and project management control of ship, petroleam,electric,dock etc.

Main Technical Specificatioin:

Accuracy : 0.5 (0.2)

PN: 1.6 , 2.5 , 4.0Mpa

Working temperature: -20 to 60, 60 to 100, 100 to 200 centigrade.
Nominal diameter" DN25 to 300mm

Body material: ZG25

Rotor material: HT250

Bearing: graphite.

Local explosion proof class for remote indication: EXIA IICT5

Flange standard: GB2506-89