LIFEBOAT AND RESCUE BOAT ACCESSORIES

Lastest CD4212-2 Lifeboat Battery Charger

ISO9001 Supplier

Class Certificate

Export Supply

The charger is specially designed for maintenanace charging of batteries used in lifeboats. Supply voltage: AC 42V Charge voltage:DC 2x12V Charge current:DC 2x5A Dimension: 243x134x80mm ...



Key Highlights

Category	Lifeboat And Rescue Boat Accessories
Standard	EN
Weight / Size	AC 42V Charge voltage:DC 2x12V Charge current:DC 2x5A Dimension:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Lifeboat And Rescue Boat Accessories	**Model / SKU**	Lastest-CD4212-2-Lifeboat-Battery-Charger
Standard	EN	**Weight / Size**	AC 42V Charge voltage:DC 2x12V Charge current:DC 2x5A Dimension:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

China Lastest CD4212-2 Lifeboat Battery Charger:

The charger is specially designed for maintenanace charging of batteries used in lifeboats.

Supply voltage: AC 42V

Charge voltage:DC 2x12V

Charge current:DC 2x5A

Dimension: 243x134x80mm

Weight:5kgs

Protection grade:IP56

Temperature:-25 to 55 centigrade.

Use Method: Connect in proper order, connect the battery, then connect the power source：42C/AC