

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## CARGO OIL HOSE

## Light Duty Fuel and Oil Hoses

Light Duty Fuel and Oil Hoses General description The Light Duty Fuel and Oil hoses are manufactured from multi-layers of polypropylene fabric and film with a weatherproof and abrasion resistant outer cov...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Cargo Oil Hose
Standard	DIN
Material	combined material
Weight / Size	Computer aided design has resulted in exceptional strength to weight rat...
Certificate	CE

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Cargo Oil Hose	Model / SKU	Light-Duty-Fuel-and-Oil-Hoses
Standard	DIN	Material	combined material
Weight / Size	Computer aided design has resulted in exceptional strength to weight ratios and extreme flexibility, giving the hoses excellent handling characteristics.	Surface	Galvanized
Certificate	CE	Warranty	12 Months unless specified otherwise
Origin	China		

#### CONTENTS

- Light Duty Fuel and Oil Hoses
- Applications
- Physical properties
- General description
- Construction
- Specification

# Light Duty Fuel and Oil Hoses

## General description

The Light Duty Fuel and Oil hoses are manufactured from multi-layers of polypropylene fabric and film with a weatherproof and abrasion resistant outer cover. The layers are held and tensioned between internal and external wire helices. Computer aided design has resulted in exceptional strength to weight ratios and extreme flexibility, giving the hoses excellent handling characteristics. This ensures ready operator acceptance and encourages good usage practice. Specializes in producing oil hoses, fuel hoses, suction hoses, pvc suction hose pipe, such as hose suction professional products. All hoses get the approval of international standards including EN 13765, BS 3492 AX + BX and BS5842, and can be supplied with factory fitted end connections to the customer's requirements.

## Applications

The Light duty fuel and oil hoses are specifically engineered for the transfer of hydrocarbons, including oils, petrol, diesel, lubricating oils, paraffin and 100% aromatics.

## Construction

Inner wire: Galvanized steel

Lining: Polypropylene

Outer cover: Polyester PVC coated blue

Outer Wire: Galvanized steel

## Physical properties

Proof pressure: 1.5 maximum working pressure

Maximum elongation: less than 10%

Maximum twist: less than 10 degree/m

Electrical resistance: less than 10 ohm

Vacuum range: 0.9bar

Min. bursting pressure: 4:1

Temperature range: -30 degree to +80degree

## Specification

Nominal diameter		Max. working pre.		Bend radius		Weight		Maximum length	
Inches	Mm	PSI	Bar	Inches	Mm	Lbs/Ft	Kg/m	Ft	m
1	25	100	7	4.90	125	0.65	0.95	65	20
1.5	40	100	7	4.90	125	0.85	1.25	65	20
2	50	100	7	5.90	150	0.95	1.40	65	20

2.5	65	100	7	5.90	150	1.20	1.80	65	20
3	80	100	7	9.85	250	1.70	2.55	65	20
4	100	100	7	11.80	300	2.30	3.40	65	20

This information is for reference only, dimensions and weight are approximate.