

SENSOR

MTC Commen Thyristor Pair of Arms Module

MTC Commen Thyristor Pair of Arms Module      IF(AV) IFSM VFM VRRM IRRM VGT IGT IH VISO TJ TC Fig.No Tpye A A V V A V mA mA V °C °C      MTC70 70 1100 ≤1.5...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|             |                                            |
|-------------|--------------------------------------------|
| Category    | Sensor                                     |
| Standard    | ISO                                        |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|          |                                      |             |                                            |
|----------|--------------------------------------|-------------|--------------------------------------------|
| Category | Sensor                               | Model / SKU | MTC-Commen-Thyristor-Pair-of-Arms-Module   |
| Standard | ISO                                  | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin      | China                                      |

China MTC Commen Thyristor Pair of Arms Module:

MTC Commen Thyristor Pair of Arms Module

| IF(AV) | IFSM | VFM  | VRRM | IRRM      | VGT | IGT | IH     | VISO   | TJ   | TC  | Fig.No |    |
|--------|------|------|------|-----------|-----|-----|--------|--------|------|-----|--------|----|
| Tpye   | A    | A    | V    | V         | A   | V   | mA     | mA     | V    | °C  | °C     |    |
| MTC70  | 70   | 1100 | ≤1.5 | 1600-2200 | ≤2  | ≤3  | 20-100 | 10-100 | 2500 | 125 | 85     | 19 |

|        |     |      |      |           |    |      |        |        |      |     |    |       |
|--------|-----|------|------|-----------|----|------|--------|--------|------|-----|----|-------|
| MTC90  | 90  | 1400 | ≤1.8 | 1600-2200 | ≤2 | ≤3.5 | 20-100 | 10-100 | 2500 | 125 | 85 | 21    |
| MTC110 | 110 | 1700 | ≤1.8 | 1600-2200 | ≤2 | ≤3.5 | 20-100 | 10-100 | 2500 | 125 | 85 | 21    |
| MTC135 | 135 | 2000 | ≤1.8 | 1600-2200 | ≤2 | ≤3.5 | 20-100 | 10-100 | 2500 | 125 | 85 | 21、22 |
| MTC160 | 160 | 2500 | ≤1.8 | 1600-2200 | ≤2 | ≤3.5 | 20-100 | 10-100 | 2500 | 125 | 85 | 22    |
| MTC200 | 200 | 3100 | ≤1.8 | 1600-2200 | ≤2 | ≤3.5 | 20-100 | 10-100 | 2500 | 125 | 85 | 24    |