MANUAL OPERATED FIRE MONITOR

Manual Fire Monitor PS60-80W

Type: PS60-80W Flow Range: 60-70-80 L/S Adjustable Working Pressure: 10 bar Max Reach @ Max Flow: 80m Range of motion: -45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Stainless Steel Material (Gear)：br...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Stainless St...
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Stainless St...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	**Model / SKU**	Manual-Fire-Monitor-PS60-80W
Standard	EN	**Material**	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Stainless Steel Material (Gear)：bronze Material (nozzle)：Aluminum Material (handwheel) ：chromate cast iron Pump requirement for minimum performance：60L/S@ 8 bar Pipe dimensions for installation:
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle ：120° Material (body)：Stainless Steel Material (Gear)：bronze Material (nozzle)：Aluminum Material (handwheel) ：chromate cast iron Pump requirement for minimum performance：60L/S@ 8 bar Pipe dimensions for installation:	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Manual Fire Monitor PS60-80W:

Type: PS60-80W
Flow Range: 60-70-80 L/S Adjustable
Working Pressure: 10 bar
Max Reach @ Max Flow: 80m
Range of motion: -45°~+90°Vert , 360°Rot
Max fog angle ：120°
Material (body)：Stainless Steel
Material (Gear)：bronze
Material (nozzle)：Aluminum
Material (handwheel) ： chromate cast iron
Pump requirement for minimum performance：60L/S@ 8 bar
Pipe dimensions for installation: 4 Inch
Monitor Inlet: DN100 flange
Monitor Outlet：2.5 inch (65mm)
Paint: Fire Red
Weight: 20KG