

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MANUAL OPERATED FIRE MONITOR

# Manual Fire Monitor PS60-80W

Type: PS60-80W Flow Range: 60-70-80 L/S Adjustable Working Pressure: 10 bar Max Reach @ Max Flow: 80m Range of motion: -45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Stainless Steel Material (Gear) : br...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Stainless St...
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Stainless St...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Manual Operated Fire Monitor	<b>Model / SKU</b>	Manual-Fire-Monitor-PS60-80W
<b>Standard</b>	EN	<b>Material</b>	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Stainless Steel Material (Gear) : bronze Material (nozzle) : Aluminum Material (handwheel) : chromate cast iron Pump requirement for minimum performance : 60L/S@ 8 bar Pipe dimensions for installation:
<b>Weight / Size</b>	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Stainless Steel Material (Gear) : bronze Material (nozzle) : Aluminum Material (handwheel) : chromate cast iron Pump requirement for minimum performance : 60L/S@ 8 bar Pipe dimensions for installation:	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

## China Manual Fire Monitor PS60-80W:

Type: PS60-80W

Flow Range: 60-70-80 L/S Adjustable

Working Pressure: 10 bar

Max Reach @ Max Flow: 80m

Range of motion: -45°~+90°Vert , 360°Rot

Max fog angle : 120°

Material (body) : Stainless Steel

Material (Gear) : bronze

Material (nozzle) : Aluminum

Material (handwheel) : chromate cast iron

Pump requirement for minimum performance : 60L/S@ 8 bar

Pipe dimensions for installation: 4 Inch

Monitor Inlet: DN100 flange

Monitor Outlet : 2.5 inch (65mm)

Paint: Fire Red

Weight: 20KG