MANUAL OPERATED FIRE MONITOR

Manual Monitor PS30-50A

ISO9001 Supplier

Class Certificate

Export Supply

Type: PS30-50A Flow Range: 30-40-50 L/S Adjustable Working Pressure: 10 bar Max Reach @ Max Flow: 65m Range of motion: -45°~+90 Vert,360 Rotation Max fog angle ：120° Material (body)：Aluminum Material (nozzle)：Alum...



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90 Vert,360 Rotation Max fog angle ：120° Material (body)：Aluminum ...
Weight / Size	-45°~+90 Vert,360 Rotation Max fog angle ：120° Material (body)：Aluminum ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	**Model / SKU**	Manual-Monitor-PS30-50A
Standard	EN	**Material**	-45°~+90 Vert,360 Rotation Max fog angle ：120° Material (body)：Aluminum Material (nozzle)：Aluminum Material (Tiller) ： 304 stainless steel with rubber handle Pump requirement for minimum performance：30L/S@ 8 bar Pipe dimensions for installation:
Weight / Size	-45°~+90 Vert,360 Rotation Max fog angle ：120° Material (body)：Aluminum Material (nozzle)：Aluminum Material (Tiller) ： 304 stainless steel with rubber handle Pump requirement for minimum performance：30L/S@ 8 bar Pipe dimensions for installation:	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Manual Monitor PS30-50A:

Type: PS30-50A
Flow Range: 30-40-50 L/S Adjustable
Working Pressure: 10 bar
Max Reach @ Max Flow: 65m
Range of motion: -45°~+90 Vert,360 Rotation
Max fog angle ：120°
Material (body)：Aluminum
Material (nozzle)：Aluminum
Material (Tiller) ： 304 stainless steel with rubber handle
Pump requirement for minimum performance：30L/S@ 8 bar
Pipe dimensions for installation: 4 Inch
Monitor Inlet : DN100 flange
Monitor Outlet：2.5 inch (65mm)
Paint: Fire Red
Weight: 16KG


jinbomarine.com