JIS MARINE STRAINER & FILTER

# Marine Cast Iron Duplex Oil Strainer JIS F7208 HU Type

ISO9001 Supplier

Class Certificate

Export Supply

Marine Cast Iron Duplex Oil Strainer JIS F7208 is used to filter the fuel oil or lubrication oil in the marine oil pipeline. Design Standard: JIS F7208-2005 Test Standard: JIS F7200-1996 Hydraulic Test ...




## Key Highlights

| | |
|---|---|
| **Category** | JIS Marine Strainer & Filter |
| **Standard** | JIS |
| **Material** | cast iron |
| **Weight / Size** | 0.4Mpa Flange size as per JIS B2220-5K or 10K Norminal Size: |
| **Certificate** | MILL CERTIFICATE |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | JIS Marine Strainer & Filter | **Model / SKU** | Marine-Cast-Iron-Duplex-Oil-Strainer-JIS-F7208-HU-Type |
| **Standard** | JIS | **Material** | cast iron |
| **Weight / Size** | 0.4Mpa Flange size as per JIS B2220-5K or 10K Norminal Size: | **Certificate** | MILL CERTIFICATE |
| **Warranty** | 12 Months unless specified otherwise | **Origin** | China |

**CONTENTS**

- China Marine Cast Iron Duplex Oil Strainer JIS F7208 HU Type:
- Main Size List(mm):
- Main Material:

## China Marine Cast Iron Duplex Oil Strainer JIS F7208 HU Type:

Marine Cast Iron Duplex Oil Strainer JIS F7208 is used to filter the fuel oil or lubrication oil in the marine oil pipeline.

Design Standard: JIS F7208-2005

Test Standard: JIS F7200-1996

Hydraulic Test Pressure: Body-0.6Mpa, Seal: 0.44Mpa

Max Working Pressure: 0.4Mpa

Flange size as per JIS B2220-5K or 10K

Norminal Size: DN25~DN125

## Main Material:

Body: Cast Iron(FC200)

Bonnet: Cast Iron (FC200)

Strainer: Carbon Steel (SS400) or Stainless Steel (SUS304 or SUS316)

Gasket: NBR

Yoke: Nodular Cast Iron (FCD450)

Air Vent Plug: Brass

Drain Plug: Brass

## Main Size List(mm):

| DN | L1 | L2 | D | C | d1 | H1 | L3 | H2 | H3 | D1 | a | D2 | H5 | L4 | L5 | t | d3 | L6 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 25 | 115 | 268 | 95 | 75 | M10 | 247 | 180 | 82.5 | 50 | 70 | 6 | 48 | 98 | 100 | 200 | 10 | 12 | 170 |
| 32 | 140 | 390 | 115 | 90 | M12 | 347 | 240 | 123 | 80 | 110 | 8 | 86 | 148 | 146 | 275 | 13 | 15 | 220 |
| 40 | 140 | 390 | 120 | 95 | M12 | 347 | 240 | 123 | 80 | 110 | 8 | 86 | 148 | 146 | 275 | 13 | 15 | 220 |

* Duplex Oil Strainer has many different type, the size can be from DN25-DN200, Flange can be manufactured according to 5K or 10K. In the list, the flange size is 5K.