

JIS MARINE STRAINER & FILTER

Marine Cast Iron Y strainer JIS F7220 5K

- ISO9001 Supplier
- Class Certificate
- Export Supply

Y Strainer is normally installed in the inlet side of the hydraulic control valve, relief valve, relief valve, inlet pressure water valves and other equipments, used to remove the impurities in the medium in order to...



Key Highlights

| | |
|---------------|--|
| Category | JIS Marine Strainer & Filter |
| Standard | JIS |
| Material | cast iron |
| Weight / Size | Body- 1.05Mpa Flange size as per JIS B2220 - 5K Marine Material: |
| Certificate | Mill Certificate |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

| | | | |
|---------------|--|-------------|--|
| Category | JIS Marine Strainer & Filter | Model / SKU | Marine-Cast-Iron-Y-strainer-JIS-F7220-5K |
| Standard | JIS | Material | cast iron |
| Weight / Size | Body- 1.05Mpa Flange size as per JIS B2220 - 5K Marine Material: | Certificate | Mill Certificate |
| Warranty | 12 Months unless specified otherwise | Origin | China |

CONTENTS

- China Marine Cast Iron Y strainer JIS F7220 5K:
- Main Size List(mm):
- Marine Material:

China Marine Cast Iron Y strainer JIS F7220 5K:



Y Strainer is normally installed in the inlet side of the hydraulic control valve, relief valve, relief valve, inlet pressure water valves and other equipments, used to remove the impurities in the medium in order to protect the equipment and pipe fittings.

Design Standard: JIS F7220-1996

Test Standard: JIS 7200-1996

Hydraulic Test Pressure: Body- 1.05Mpa

Flange size as per JIS B2220 - 5K

Marine Material:

- 1.Body-Cast Iron (FC200)
- 2.Bonnet-Cast Iron (FC200)
- 3.Strainer-Stainless Steel (SUS304)
- 4.Gasket:non-asbestos

Main Size List(mm):

| DN | d | L | D | C | Hole (n-d) | t | H |
|-----|-----|-----|-----|-----|------------|----|-----|
| 20 | 20 | 200 | 85 | 65 | 4-12 | 14 | 127 |
| 25 | 25 | 225 | 95 | 75 | 4-12 | 14 | 155 |
| 32 | 32 | 260 | 115 | 90 | 4-15 | 16 | 164 |
| 40 | 40 | 280 | 120 | 95 | 4-15 | 16 | 180 |
| 50 | 50 | 320 | 130 | 105 | 4-15 | 16 | 208 |
| 65 | 65 | 350 | 155 | 130 | 4-15 | 18 | 253 |
| 80 | 80 | 373 | 180 | 145 | 4-19 | 18 | 268 |
| 100 | 100 | 390 | 200 | 165 | 8-19 | 20 | 286 |
| 125 | 125 | 410 | 235 | 200 | 8-19 | 20 | 295 |
| 150 | 150 | 430 | 265 | 230 | 8-19 | 20 | 318 |