

RUDDER PROPELLERS

Marine Deck Type Rudder Propeller

It can be mechanically or hydraulically raised or lowered in vertical direction very convenient. For maintenance purposes, the rudder thruster can be pivoted out of the water to the rear hydraulically or mechani...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

| | |
|-------------|------------------------|
| Category | Rudder Propellers |
| Standard | EN |
| Material | Cu |
| Certificate | ABS,BV,DNV,LR,CCS etc. |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

| | | | |
|-------------|------------------------|-------------|--------------------------------------|
| Category | Rudder Propellers | Model / SKU | Marine-Deck-Type-Rudder-Propeller |
| Standard | EN | Material | Cu |
| Certificate | ABS,BV,DNV,LR,CCS etc. | Warranty | 12 Months unless specified otherwise |
| Origin | China | | |

CONTENTS

- China Marine Deck Type Rudder Propeller:
 - Features:
 - Specification:

China Marine Deck Type Rudder Propeller:

It can be mechanically or hydraulically raised or lowered in vertical direction very convenient.

For maintenance purposes, the rudder thruster can be pivoted out of the water to the rear hydraulically or mechanically by hand.



Features:

- 1.The steering mode can be hydraulic motor-driven or electrical motor-driven.Drive power from 20KW- 2250KW
- 2.Propeller is fixed pitch and open or with nozzle. Propeller diameter from 500 mm-2600 mm.
- 3.Application: tug boat, harbor workboat, service ship, ferry and engineering ship.
- 4.Certificate: CCS, BV, NKK, ABS, DNV, KR, GL, LR, etc.

Specification:

| Model | Input power | Input speed | Propeller diameter | Propeller type | Max force |
|-------|-------------|-------------|--------------------|----------------|-----------|
| | (kW) | (rpm) | (mm) | | (T) |
| RP | 20-150 | 1500-2500 | 500/600/700 | FPP | 3.4 |
| RP | 150-250 | 1500-2350 | 700/800/900 | FPP | 2.9 |
| RP | 230-480 | 1200-2350 | 900/1000/1100 | FPP | 7.4 |
| RP | 420-690 | 830-1800 | 1200/1300/1400 | FPP/ CPP | 11.1 |
| RP | 650-980 | 830-1800 | 1500/1600/1700 | FPP/ CPP | 16.1 |
| RP | 950-1500 | 830-1500 | 1900/2000/2100 | FPP/ CPP | 24.3 |
| RP | 1320-1750 | 750-1500 | 2200/2300/2400 | FPP/ CPP | 29.3 |
| RP | 1650-2250 | 550-1200 | 2400/2500/2600 | FPP/ CPP | 36.9 |