

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

JIS MARINE GLOBE VALVE

Marine Forged Steel Globe Valve JIS F7329 40K

ISO9001 Supplier

Class Certificate

Export Supply

Marine Forged Steel 40K Globe Valve JIS F7329 is the stop valve used on the marine steam, water supply, fuel oil and lubrication oil pipe system to shut off/turn on the medium and control the flow rate in the 40K pipe sy...



Key Highlights

Category	JIS Marine Globe Valve
Standard	JIS
Material	Forged Steel
Weight / Size	Disc---Stainless Steel Main Size:
Certificate	CCS,DNV,GL, LR, ABS, BV, NK,KR,RINA

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	JIS Marine Globe Valve	Model / SKU	Marine-Forged-Steel-Globe-Valve-JIS-F7329-40K
Standard	JIS	Material	Forged Steel
Weight / Size	Disc---Stainless Steel Main Size:	Certificate	CCS,DNV,GL, LR, ABS, BV, NK,KR,RINA
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Marine Forged Steel Globe Valve JIS F7329 40K:
- Technical Specification:
- Main Material:
- Type:
- Max Working Pressure:
- Main Size:

China Marine Forged Steel Globe Valve JIS F7329 40K:

Marine Forged Steel 40K Globe Valve JIS F7329 is the stop valve used on the marine steam, water supply, fuel oil and lubrication oil pipe system to shut off/turn on the medium and control the flow rate in the 40K pipe system.

Type:

S type---Screw Thread Type (DN6 & DN10)

U type---Union Type (DN6 & DN10)

W type--Socket Weld Type (DN6~DN25)

F type---Flange Type (DN15, DN20, DN25)

Technical Specification:

- 1.Design and manufacturing standard: JIS F7329
- 2.Test Standard: JIS F7400
3. Suitable Medium: Steam, Fresh Water, Fuel Oil, Lubrication Oil
4. Hydraulic Test: 9.3Mpa for body, 6.82Mpa for Seat.

Max Working Pressure:

Fluid Status	Max Pressure
Steam of 425°C	4.0
Steam of 400°C	4.6
Steam of 350°C	5.2
Steam of 300°C or less	5.7
Air,Gas,oil & pulsation water	6.2

Main Material:

1. Body---Forged Steel
2. Stem---Stainless Steel
3. Disc---Stainless Steel

Main Size:

Type	IMPA CODE	Size	L	L1	L2	L3	K	D	C	n	h	t	H	B2	D3	Weight
Type "S"	750641	6	-	42	38	51	12	-	-	-	-	-	152	30	M20x1.5	1.6
	750642	10	-	51	45	63	16	-	-	-	-	-	152	41	M42x2	2.0
Type "U"	750646	6	84	102	-	-	-	-	-	-	-	-	152	30	-	1.8
	750647	10	102	126	-	-	-	-	-	-	-	-	152	41	-	2.3

Type "W"	750651	6	84	-	-	-	-	-	-	-	-	-	152	-	-	1.5
	750652	10	102	-	-	-	-	-	-	-	-	-	152	-	-	2.0
	750653	15	130	-	-	-	-	-	-	-	-	-	205	-	-	3.6
	750654	20	150	-	-	-	-	-	-	-	-	-	230	-	-	5.2
	750655	25	170	-	-	-	-	-	-	-	-	-	255	-	-	7.5
Type "F"	750661	15	150	-	-	-	-	115	80	4	19	20	215	-	-	5.2
	750662	20	170	-	-	-	-	120	85	4	19	20	250	-	-	6.8
	750663	25	200	-	-	-	-	130	95	4	19	22	270	-	-	8.9