

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

OTHER MARINE PUMP

Marine Macerator Pump 02-Series

Marine Macerator Pump 02-Series New design SEAFLO 02-Series RV macerator pump unit is the ideal waste emptying solution for your RV. With the Quick-Connect RV fitting, this pump easily attaches and remo...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Other Marine Pump
Standard	DIN
Weight / Size	STANDARD PUMP CONFIGURATIONS Model Voltage Open Flow (GPM/LPM) Dimension...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Other Marine Pump	Model / SKU	Marine-Macerator-Pump-02-Series
Standard	DIN	Weight / Size	STANDARD PUMP CONFIGURATIONS Model Voltage Open Flow (GPM/LPM) Dimensions Impeller Ports Max Draw(A) SFMP1-120-02 12V 12.0/45.0 11.6"x5.79"x5.2" 294.5x147x132mm Rubber & Copper 3" (75 mm) RV Connector 1" Hose Barb 12.0 A SFMP2-120-02 24V 12.0/45.0 11.6"x5.79"x5.2" 294.5x147x132mm Rubber & Copper 3" (75 mm) RV Connector 1" Hose Barb 7.0 A PERFORMANCE PRESSURE FLOW CURRENT PSI BAR GPM LPM AMPS 0 0 10.0 41.0 12.2 4 0.28 8.00 30.3 13.1 8 0.55 6.13 23.2 13.8 12 0.83 4.07 15.4 14.5 16 1.10 0 0 0
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ Marine Macerator Pump 02-Series ■ STANDARD PUMP CONFIGURATIONS ■ PERFORMANCE
-----------------	--

Marine Macerator Pump 02-Series



New design SEAFLO 02-Series RV macerator pump unit is the ideal waste emptying solution for your RV. With the Quick-Connect RV fitting, this pump easily attaches and removes in seconds. It cleanly handles both the black and the grey water from your holding tanks with this self priming, powerful macerator pump. The pump housing is designed to connect onto the standard three inch waste outlet.



STANDARD PUMP CONFIGURATIONS

Model	Voltage	Open Flow (GPM/LPM)	Dimensions	Impeller	Ports	Max Draw(A)
SFMP1-120-02	12V	12.0/45.0	11.6"x5.79"x5.2" 294.5x147x132mm	Rubber & Copper	3" (75 mm) RV Connector 1" Hose Barb	12.0 A
SFMP2-120-02	24V	12.0/45.0	11.6"x5.79"x5.2" 294.5x147x132mm	Rubber & Copper	3" (75 mm) RV Connector 1" Hose Barb	7.0 A

PERFORMANCE

PRESSURE		FLOW		CURRENT
PSI	BAR	GPM	LPM	AMPS
0	0	10.0	41.0	12.2
4	0.28	8.00	30.3	13.1
8	0.55	6.13	23.2	13.8
12	0.83	4.07	15.4	14.5
16	1.10	0	0	0