

## PUMP MOTOR AND ACCESSORIES

# Mechanical seals for CLZ series pump 50CLZ-30

ISO9001 Supplier

Class Certificate

Export Supply

Double end/balanced/arbitrary/multi-spring structure With the same design performance as the H7 series, other installation sizes (d1<100mm), except the installation length of the drive seat, conform to DIN24960 stand...

**Key Highlights**

<b>Category</b>	Pump Motor And Accessories
<b>Standard</b>	DIN
<b>Material</b>	stainless steel
<b>Weight / Size</b>	Double end/balanced/arbitrary/multi-spring structure With the same design...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

**Technical Specifications**

<b>Category</b>	Pump Motor And Accessories	<b>Model / SKU</b>	Mechanical-seals-for-CLZ-series-pump-50CLZ-30
<b>Standard</b>	DIN	<b>Material</b>	stainless steel
<b>Weight / Size</b>	Double end/balanced/arbitrary/multi-spring structure With the same design performance as the H7 series, other installation sizes (d1<100mm), except the installation length of the drive seat, conform to DIN24960 standard.	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China



## China Mechanical seals for CLZ series pump 50CLZ-30:

Double end/balanced/arbitrary/multi-spring structure

With the same design performance as the H7 series, other installation sizes ( $d1 < 100\text{mm}$ ), except the installation length of the drive seat, conform to DIN24960 standard.

Work scope:

Gauge: 14 ~ 200 mm

Pressure:  $\leq 4.0\text{mpa}$

Temperature:  $-50 \sim 220^\circ\text{C}$

Linear velocity:  $\leq 20\text{ m/s}$

Axial cross momentum:

D1 100 or less:  $+ / - 0.5\text{ mm}$

D1  $> 100$  :  $+ / - 2.0\text{ mm}$

Seal face: graphite, silicon carbide, tungsten carbide, alumina

Auxiliary seal: nitrile rubber, fluoro rubber, ethylene rubber, PTFE

Metal components: stainless steel

