

**MANUAL OPERATED FIRE MONITOR**

# Moveable Fire Monitor PSY30-80

Type: PSY80A Weight : Approx 20KG Flow Range: 10-80 L/S Automatic Nozzle Working Pressure: 10 bar Max Reach @ Max Flow: 80m Range of motion: 0°~+90°Vert , 360°Rot Max fog angle : 120° Monitor Outlet : 2.5 inch (65mm) ...

ISO9001 Supplier

Class Certificate


Export Supply



### Key Highlights

<b>Category</b>	Manual Operated Fire Monitor
<b>Standard</b>	EN
<b>Material</b>	0°~+90°Vert , 360°Rot Max fog angle : 120° Monitor Outlet : 2.5 inch (65mm)...
<b>Weight / Size</b>	PSY80A Weight : Approx 20KG Flow Range:
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Manual Operated Fire Monitor	<b>Model / SKU</b>	Moveable-Fire-Monitor-PSY30-80
<b>Standard</b>	EN	<b>Material</b>	0°~+90°Vert , 360°Rot Max fog angle : 120° Monitor Outlet : 2.5 inch (65mm) Monitor Inlet : 2.5 inch X 2 couplings Material (body) : Aluminum Material (Gear) : Aluminum Material (nozzle) : Aluminum Horizontal Control : Lever Action Rotational Lock Vertical Control : Handwheel (6 Inch, Injection Molded Nylon) Pump requirement for minimum performance : 10L/S@ 8 bar Inlet coupling is hose anti-knot ,360 degree rotatable Foam attachment is available for foam fire fighting Paint:
<b>Weight / Size</b>	PSY80A Weight : Approx 20KG Flow Range:	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

## China Moveable Fire Monitor PSY30-80:

Type: PSY80A

Weight : Approx 20KG

Flow Range: 10-80 L/S Automatic Nozzle

Working Pressure: 10 bar

Max Reach @ Max Flow: 80m

Range of motion: 0°~+90°Vert , 360°Rot

Max fog angle : 120°

Monitor Outlet : 2.5 inch (65mm)

Monitor Inlet : 2.5 inch X 2 couplings

Material (body) : Aluminum

Material (Gear) : Aluminum

Material (nozzle) : Aluminum

Horizontal Control : Lever Action Rotational Lock

Vertical Control : Handwheel (6 Inch, Injection Molded Nylon)

Pump requirement for minimum performance : 10L/S@ 8 bar

Inlet coupling is hose anti-knot ,360 degree rotatable

Foam attachment is available for foam fire fighting

Paint: Fire Red

