

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## RUBBER SHEET

## NBR Nitrile Rubber Sheet

CR Neoprene Rubber Sheet Specification: 0.8 to 50mm thickness. 0.2 to 3 m width. 1 to 20 m length. Density:1.3 to 1.5g/cm<sup>3</sup> . Tensile strength: 500 to 1500psi Elongation: 300% to 400% Hardnes...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Rubber Sheet
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Rubber Sheet	Model / SKU	NBR-Nitrile-Rubber-Sheet
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

#### CONTENTS

- China NBR Nitrile Rubber Sheet:
- Features:
- Application:

### China NBR Nitrile Rubber Sheet:

CR Neoprene Rubber Sheet

Specification: 0.8 to 50mm thickness. 0.2 to 3 m width. 1 to 20 m length.

Density:1.3 to 1.5g/cm<sup>3</sup> .

Tensile strength: 500 to 1500psi



Elongation: 300% to 400%

Hardness:40 to 80  $\pm$ 5 Shore-A

## Application:

Used for high resistant to oil and solvent product.

Used as sealing in oil tank and oil pipeline.

Suitable for making composite antistatic.

## Features:

Excellent sealing.

Wear resistance and aging.

Temperature resistance.

High resistant to mineral acids,alkali and salts.