

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE COMMUNICATION EQUIPMENT

# NEB-1000 EPIRB

FEATURES: Designed to use for alert search and rescue service at sea. Confirming to IMO and IEC rules. Location accuracy within 10m, thanks to built-in GNSS receiver used. Automatic release device activated underwat...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

**Category** Marine Communication Equipment

**Standard** EN

**Certificate** CCS,DNV-GL,VR type approval certificate.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

<b>Category</b>	Marine Communication Equipment	<b>Model / SKU</b>	NEB-1000-EPIRB
<b>Standard</b>	EN	<b>Certificate</b>	CCS,DNV-GL,VR type approval certificate.
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

CONTENTS

■ FEATURES:

■ Specification:

### FEATURES:

- Designed to use for alert search and rescue service at sea. Confirming to IMO and IEC rules.
- Location accuracy within 10m, thanks to built-in GNSS receiver used.
- Automatic release device activated underwater 4 meters.
- Self-protective device used to avoid possible false alarms.
- Self-test function applicable.
- 406MHz transmission together with homing 121MHz.
- Cospas-Sarsat approved.
- Creative design for easy operation.

Automatic power cut when test completed.

Multiple protection to avoid false alert.

Lower power consumption for longer working hours.

## Speification:

<b>General</b>	
Model:	NEB-1000 / NEB-2000C
Case Material:	Special ABS+PC
Color:	Orange
IP Grade:	IP67
Buoyant:	Yes
Deployment:	Automatic hydrostatic release or Manual switch control
Accessories:	Hydrostatic Release Unit
<b>Physical</b>	
Weight:	1.5 kg (Beacon), 1.6 kg (Container)
Size:	116 x 116x 692 mm (Beacon), 220 x 415 x 141 mm (Container)
<b>406 MHz Transmitter</b>	
Frequency:	406.040MHz
Output Power:	5W ± 2dB
<b>121.5 MHz Homer</b>	
Frequency:	121.5MHz
Output Power:	50mW ± 3dB
<b>GPS Receiver</b>	
Type:	Built-in GNSS antenna
Center Frequency:	L1-1575.42MHz
Satellites Tracked:	50
<b>Battery</b>	
Type:	NBT300 / NBT400
Total Voltage Rating:	14.4 V (4ea x 3.6V each)
Storage:	5 years on board (see Note 1)
Operating:	≥48hrs. (-20°C)
<b>Environment</b>	
Operating Temperature:	-20°C ~ +55°C
Storage Temperature:	-30°C ~ +70°C