

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MEDIUM PRESSURE AIR COOLED MARINE AIR COMPRESSOR

# NWP40L Two Stages Medium Pressure Air Cooled Marine Air Compressor

ISO9001 Supplier

Class Certificate

Export Supply

Design Particulars : Max Pressure 4.0MPa V-type, Low vibration Easy installation and easy maintenance Air-cooled type, avoid costs for water circuit Lubrication system: splash/pressure oil ...



### Key Highlights

<b>Category</b>	Medium Pressure Air Cooled Marine Air Compressor
<b>Standard</b>	EN
<b>Weight / Size</b>	Speed (r/min) Capacity (m3/h) Power required (KW) Power of motor (KW) Co...
<b>Certificate</b>	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Medium Pressure Air Cooled Marine Air Compressor	<b>Model / SKU</b>	NWP40L-Two-Stages-Medium-Pressure-Air-Cooled-Marine-Air-Compressor
<b>Standard</b>	EN	<b>Weight / Size</b>	Speed (r/min) Capacity (m3/h) Power required (KW) Power of motor (KW) Cooling air required (L/min ) Dimension (LxWxH) Weight (kg) NWP40L 3 2 2 1150 30.5 6.6 7.5 31 1220*720*778 300 1450 39 8.3 11 38 1750 45 10.1 11 47 NWP50L 3.0 2 2 1150 38 8.5 11 39 1220*720*778 300 1450 48.5 10.5 11 49 1750 58.5 12.7 15 59 NWP62L 3 2 2 1150 46 9.8 11 45 1220*720*778 330 1450 58 12.5 15 58 1750 70 15.1 18.5 70
<b>Certificate</b>	CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ Design Particulars :</li> <li>■ Technical Data : Model Pressure (MPa) Stages Cylinders Qty. Speed (r/min) Capacity (m3/h) Power required (KW) Power of motor (KW) Cooling air required (L/min ) Dimension (LxWxH) Weight (kg) NWP40L 3 2 2 1150 30.5 6.6 7.5 31 1220*720*778 300 1450 39 8.3 11 38 1750 45 10.1 11 47 NWP50L 3.0 2 2 1150 38 8.5 11 39 1220*720*778 300 1450 48.5 10.5 11 49 1750 58.5 12.7 15 59 NWP62L 3 2 2 1150 46 9.8 11 45 1220*720*778 330 1450 58 12.5 15 58 1750 70 15.1 18.5 70</li> </ul>
-----------------	---

## Design Particulars :

Max Pressure 4.0MPa

V-type, Low vibration

Easy installation and easy maintenance

Air-cooled type, avoid costs for water circuit

Lubrication system: splash/pressure oil lubrication

Performance data with 5% tolerance

Standard voltage and frequency: 380V/50HZ, 440V/60HZ

## Technical Data :

Model	Pressure (MPa)	Stages	Cylinders Qty.	Speed (r/min)	Capacity (m <sup>3</sup> /h)	Power required (KW)	Power of motor (KW)	Cooling air required (L/min)	Dimension (LxWxH)	Weight (kg)
NWP 40L	3	2	2	1150	30.5	6.6	7.5	31	1220*720*778	300
				1450	39	8.3	11	38		
				1750	45	10.1	11	47		
NWP 50L	3.0	2	2	1150	38	8.5	11	39	1220*720*778	300
				1450	48.5	10.5	11	49		
				1750	58.5	12.7	15	59		
NWP 62L	3	2	2	1150	46	9.8	11	45	1220*720*778	330
				1450	58	12.5	15	58		
				1750	70	15.1	18.5	70		