

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE NAVIGATION SIGNAL LIGHT

Navigation Signal Light CXH-21P

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Navigation Signal Light
Standard	ISO
Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 12V 24V Power 25W 25W Luminous Intensity 40cd 60cd Lamp Holder B...
Certificate	CCS Type Approval Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Navigation-Signal-Light-CXH-21P
Standard	ISO	Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 12V 24V Power 25W 25W Luminous Intensity 40cd 60cd Lamp Holder Bay15d Protection Class IP56 Cable Outside Diameter Dia.9 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-21P 2n.m 112.5o Green 1.2KGS Port Light CXH2-21P 3n.m 112.5o Red 1.2KGS Masthead Light CXH3- 21P 5n.m 225o White 1.2KGS Stern Light CXH4-21P 2n.m 135o White/Yellow 1.2KGS All-round- Light CXH6-21P 3n.m 360o Red/green/white 1.2KGS	Certificate	CCS Type Approval Certificate
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Navigation Signal Light CXH-21P:
- Standards:

- Product Advantage:
- Main Specification:


China Navigation Signal Light CXH-21P:



The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

Product Advantage:

1. The signal lights have the seal structure, waterproof under the extreme enviroment.



2. The shell is made of high-strength engineering plastic PA+GF, the lamp shade use injection of PC, lens hood of good quality
3. Special light bulb with average life up to 700hrs.
4. Working Temperature:-30°C-55°C

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:



Voltage	12V	24V
Power	25W	25W
Luminous Intensity	40cd	60cd
Lamp Holder	Bay15d	
Protection Class	IP56	
Cable Outside Diameter	Dia.9	

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-21P	2n.m	112.5°	Green	1.2KGS
Port Light	CXH2-21P	3n.m	112.5°	Red	1.2KGS
Masthead Light	CXH3-21P	5n.m	225°	White	1.2KGS
Stern Light	CXH4-21P	2n.m	135°	White/Yellow	1.2KGS
All-round- Light	CXH6-21P	3n.m	360°	Red/green/white	1.2KGS

