DIESEL ENGINE DRIVEN WATER PUMP

New model diesel water pump

New model diesel water pump Parameter New model diesel water pump Set Model 50KB-2 80KB-3 ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Diesel engine driven water pump
Standard	EN
Weight / Size	Head lift(m) 15 13 Suction.Time 80s/4m 120s/4m Max.Suction head(m) 8 8 M...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Diesel engine driven water pump	**Model / SKU**	New-model-diesel-water-pump
Standard	EN	**Weight / Size**	Head lift(m) 15 13 Suction.Time 80s/4m 120s/4m Max.Suction head(m) 8 8 Max.Capacity(m3/h) 28 50 Max.Head lift(m) 29 25 Engine Engine model 170F 170F Engine type Single cylinder,4-stroke,air cooled diesel engine BorexStroke(mm) 70x55 70x55 Displacement(ml) 211 211 Rated power(kw) 2.5 2.5 Max.output power(HP) 4 4 Rated spee(RPM) 3000 3000 Mix.Spee(RPM) <1300 <1300 Fuel consumption ratio(g/kw.h) <280.2 <280.2 Fuel type 0#,-10# diesel oil starting method Recoil start Fuel tank capacity(L) 2.65 2.65 Oil capacity(L) 0.75 0.75 Pack Packing size(mm) 500x425x505 500x425x505 Net weight(Kgs) 29.5 32.5 Gross weight(Kgs) 31.5 34.5 20FT Qty 228 228
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- New model diesel water pump
- Parameter

New model diesel water pump

Parameter

New model diesel water pump

Set	Model	50KB-2	80KB-3
	Name	New model diesel pump	
	Inlet/Outlet diameter	50mm(2")	80mm(3")
	Cont. Capacity(m3/h)	22	30
	Cont. Head lift(m)	15	13
	Suction.Time	80s/4m	120s/4m
	Max.Suction head(m)	8	8
	Max.Capacity(m3/h)	28	50
	Max.Head lift(m)	29	25
Engine	Engine model	170F	170F
	Engine type	Single cylinder,4-stroke,air cooled diesel engine	
	BorexStroke(mm)	70x55	70x55
	Displacement(ml)	211	211
	Rated power(kw)	2.5	2.5
	Max.output power(HP)	4	4
	Rated spee(RPM)	3000	3000
	Mix.Spee(RPM)	<1300	<1300
	Fuel consumption ratio(g/kw.h)	<280.2	<280.2
	Fuel type	0#,-10# diesel oil	
	starting method	Recoil start	
	Fuel tank capacity(L)	2.65	2.65
	Oil capacity(L)	0.75	0.75
Pack	Packing size(mm)	500x425x505	500x425x505
	Net weight(Kgs)	29.5	32.5
	Gross weight(Kgs)	31.5	34.5
	20FT Qty	228	228