

MOORING EQUIPMENT ACCESSORIES

Non Asbestos Woven Brake Lining with Resin(BXS-O)

ISO9001 Supplier

Class Certificate

Export Supply

Non Asbestos Woven Brake Lining with Resin(BXS-O) General description We select new type non asbestos yarn which contains brass wire, viscose fiber, glass fiber, aramid fiber act. The yarns are woven by the advanced I...



Key Highlights

Category	Mooring Equipment Accessories
Standard	EN
Material	NON asbestos woven
Certificate	ISO9001-2008

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Mooring Equipment Accessories	Model / SKU	Non-Asbestos-Woven-Brake-Lining-with-Resin-BXS-O
Standard	EN	Material	NON asbestos woven
Certificate	ISO9001-2008	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Non Asbestos Woven Brake Lining with Resin(BXS-O)
 - Performance of BXS-O
- General description
 - Production information

Non Asbestos Woven Brake Lining with Resin(BXS-O)

General description

We select new type non asbestos yarn which contains brass wire, viscose fiber, glass fiber, aramid fiber act. The yarns are woven by the advanced loom machinery, used specially developed and produced macromolecule resin, through high temperature, low temperature workmanship. The product has high performance of wear resistance, low wear rate, high tensile strength, good softness, high temperature resistance, corrosion resistance, oil resistance, long service life and impact resistance etc. The products are pollution free and environmental.

Performance of BXS-O

Temperature	Coefficient of friction	Wear rate(V) cm3/N.m
100 c	0.40--0.65	≤0.7X10-7
150 c	0.35--0.65	≤0.9X10-7
200 c	0.32--0.60	≤1.1X10-7

Production information

Thickness: 5--30mm

Width: Max. 500mm

Length: 10m/roll, 15m/roll, 20m/roll

Color: orange

Package: opp bag and woven bag

Used for marine windlass and winch etc.