SENSOR

# OMK-08 Type Oil Water Interface Detector

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: This equipment is consists of sensor and amplifier,its physical principle is ,when ultrasonic get through the different liquid or interface, the energy will met attenuation or refraction,in thi...




## Key Highlights

| | |
|---|---|
| **Category** | Sensor |
| **Standard** | EN |
| **Weight / Size** | OMK-08A OMK-08B Voltage AC110V/220V AC220/240V DC24V Power consumption 6... |
| **Certificate** | CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC. |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | Sensor | **Model / SKU** | OMK-08-Type-Oil-Water-Interface-Detector |
| **Standard** | EN | **Weight / Size** | OMK-08A OMK-08B Voltage AC110V/220V AC220/240V DC24V Power consumption 6VA Relay output DPDT Contact capacity AC230V 5A Size 200x120x75 Shell Polycarbonate IP65 Installation size 188x88 |
| **Certificate** | CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC. | **Warranty** | 12 Months unless specified otherwise |
| **Origin** | China | | |

**CONTENTS**

- Product Description:
- Main Technical Specification:
- Features:

## Product Description:

This equipment is consists of sensor and amplifier,its physical principle is ,when ultrasonic get through the different liquid or interface, the energy will met attenuation or refraction,in this way,to get the oil and water interface detected.

## Features:

No moving parts.

No fixed forms.

The installation is very convenient.

Its performance is stable and reliable.

## Main Technical Specification:

| Model No. | OMK-08A | OMK-08B |
|---|---|---|
| Voltage | AC110V/220V<br>AC220/240V | DC24V |
| Power consumption | 6VA | |
| Relay output | DPDT | |
| Contact capacity | AC230V 5A | |
| Size | 200x120x75 | |
| Shell | Polycarbonate IP65 | |
| Installation size | 188x88 | |