

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

OIL SPILL DISPOSE DEVICE

Oil Absorbent

Oil absorbent It is made of oil absorbent felt and designed for absorbing oil on water. Compared with general boom, it is more convenient to be deployed or withdrawn. At the meantime, it has the ability of conta...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Oil Spill Dispose Device
Standard	EN
Weight / Size	Technical parameter Mode Mass(kg/m) Width(m) Diameter(mm) Length per sec...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Oil Spill Dispose Device	Model / SKU	Oil-Absorbent
Standard	EN	Weight / Size	Technical parameter Mode Mass(kg/m) Width(m) Diameter(mm) Length per sec(m) Max absorbent(kg/m) XTLY-220 2.15 220 10 22 XTLP-900 1.25 0.9 20 13 XTLY-200 0.6 200 3 7
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Oil absorbent

■ Technical parameter



Oil absorbent

It is made of oil absorbent felt and designed for absorbing oil on water. Compared with general boom, it is more convenient to be deployed or withdrawn. At the meantime, it has the ability of containing and reclaiming oil spill. In certain circumstances, it can be used for replacing oil boo, and skimmer. Joint is arranged at both ends of each column, which can be connected into length needed.



Technical parameter

Mode	Mass(kg/m)	Width(m)	Diameter(mm)	Length per sec(m)	Max absorbent(kg/m)
XTLY-220	2.15	220	10	22	
XTLP-900	1.25	0.9	20	13	
XTLY-200	0.6	200	3	7	