

**GEAR PUMP**

# Oil Gear Pumps

Oil Gear Pumps SEAFLO gear pumps are positive displacement pumps, capable of operation in either direction. They may be used to perform a variety of oil transfer applications (DO NOT USE FOR G...

ISO9001 Supplier

Class Certificate

Export Supply


	<h3>Key Highlights</h3>	
	Category	Gear Pump
	Standard	EN
	Material	We use robust motors, stainless steel shafts and rugged metal gears.
	Weight / Size	PUMP Type Thermally Protected, High Quality Efficient Motor Max Recommend...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>		



Technical Specifications			
<b>Category</b>	Gear Pump	<b>Model / SKU</b>	Oil-Gear-Pumps
<b>Standard</b>	EN	<b>Material</b>	We use robust motors, stainless steel shafts and rugged metal gears.
<b>Weight / Size</b>	PUMP Type Thermally Protected, High Quality Efficient Motor Max Recommended Temperature 60° C (140° F) Priming Capabilities 3.2 feet (1 m) suction lift Head 9.8 feet (3 m) suction lift Inlet/Outlet Ports 3/8" (10mm) FNPT Weight 5.46 lbs (2.48kg) MOTOR Leads Wire leads Duty Cycle Intermittent Max.Amp Draw 10 A STANDARD PUMP CONFIGURATIONS Model Voltage Open Flow ( GPM/LPM) Dimensions Impeller Ports Max Draw(A) SFGP1-032-003-01 12V 3.2 / 12.0 7.68" x 5.12 "x 4.25' 195 x 130 x 108mm Copper 3/8" FNPT 10.0 SFGP2-032-003-01 24V 3.2 / 12.0 7.68" x 5.12 "x 4.25' 195 x 130 x 108mm Copper 3/8" FNPT 6.0	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

<b>CONTENTS</b>	■ Oil Gear Pumps	■ Parameter pump and motor:
	■ STANDARD PUMP CONFIGURATIONS	

## Oil Gear Pumps



SEAFLO gear pumps are positive displacement pumps, capable of operation in either direction. They may be used to perform a variety of oil transfer applications (DO NOT USE FOR GASOLINE or other combustible fluids). We use robust motors, stainless steel shafts and rugged metal gears. Our tough design provides performance that you can rely on for years.

## Parameter pump and motor:

PUMP	
Type	Thermally Protected,High Quality Efficient Motor
Max Recommended Temperature	60° C (140° F)
Priming Capabilities	3.2 feet (1 m) suction lift
Head	9.8 feet (3 m) suction lift
Inlet/Outlet Ports	3/8" (10mm) FNPT
Weight	5.46 lbs (2.48kg)

MOTOR	
Leads	Wire leads
Duty Cycle	Intermittent
Max.Amp Draw	10 A

## STANDARD PUMP CONFIGURATIONS

Model	Voltage	Open Flow ( GPM/LPM)	Dimensions	Impeller	Ports	Max Draw(A)
SFGP1-032-003-01	12V	3.2 / 12.0	7.68" x 5.12 "x 4.25' 195 x 130 x 108mm	Copper	3/8" FNPT	10.0
SFGP2-032-003-01	24V	3.2 / 12.0	7.68" x 5.12 "x 4.25' 195 x 130 x 108mm	Copper	3/8" FNPT	6.0