

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

OIL HOSE

Oil Suction And Discharge hose

Handle petroleum products up to 50% aromatics on marine docks ,ships, and barges.
Flexible, Abrasion, Aging, Oil, Weather Proof, Ozone resistance Working Temperature:
 -20 TO 120 °C Safety Factor: 1...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Oil Hose
Standard	EN
Material	NR, SBR
Weight / Size	CR and NBR Blend Specification ID OD Length Bend radius WP Weight in mm ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Oil Hose	Model / SKU	Oil-Suction-And-Discharge-hose
Standard	EN	Material	NR, SBR
Weight / Size	CR and NBR Blend Specification ID OD Length Bend radium WP Weight in mm in mm ft m in mm Psi Kg/cm ² Kg/m 2 50.8 2.575 65.4 66-200 20-60 12 300 225 15 1.84 2 1/2 63.5 3.217 81.7 66-200 20-60 16 400 225 15 2.8 3 76.2 3.764 95.6 66-200 20-60 18 450 225 15 3.48 4 101.6 4.803 122 66- 200 20-60 24 600 225 15 4.74 5 127 5.945 151 66-200 20-60 30 750 225 15 6.85 6 152.4 6.976 177.2 66-200 20-60 36 900 225 15 8.33 8 203.2 9.197 233.6 66-200 20-60 48 1200 225 15 13.51 10 254 11.433 290.4 33-100 10-30 60 1500 225 15 19.31 12 304.8 13.638 346.4 33-100 10-30 72 1800 225 15 26.36	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> China Oil Suction And Discharge hose: Specification
-----------------	--

China Oil Suction And Discharge hose:

Handle petroleum products up to 50% aromatics on marine docks ,ships, and barges.

Flexible, Abrasion, Aging, Oil, Weather Proof, Ozone resistance

Working Temperature: -20 TO 120 °C

Safety Factor: 1:3

- Hose Lining: NBR
- Reinforcement Layer: Tire Cord With Helix Wire
- Cover Rubber Layer: CR and NBR Blend

Specification

ID		OD		Length		Bend radium		WP		Weight
in	mm	in	mm	ft	m	in	mm	Psi	Kg/cm ²	Kg/m
2	50.8	2.575	65.4	66-200	20-60	12	300	225	15	1.84

2 1/2	63.5	3.217	81.7	66-200	20-60	16	400	225	15	2.8
3	76.2	3.764	95.6	66-200	20-60	18	450	225	15	3.48
4	101.6	4.803	122	66-200	20-60	24	600	225	15	4.74
5	127	5.945	151	66-200	20-60	30	750	225	15	6.85
6	152.4	6.976	177.2	66-200	20-60	36	900	225	15	8.33
8	203.2	9.197	233.6	66-200	20-60	48	1200	225	15	13.51
10	254	11.433	290.4	33-100	10-30	60	1500	225	15	19.31
12	304.8	13.638	346.4	33-100	10-30	72	1800	225	15	26.36