NEK606 CABLE

P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable (NEK606)

P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable Cable Construction Classification Code C...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	NEK606 Cable
Standard	DIN
Material	Tinned Copper/EPR insulation/SHF2 Sheath or SHF Mud
Weight / Size	P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable Cable Constructi...
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	NEK606 Cable	**Model / SKU**	P18-RU-0-6-1KV-Halogen-free-Flame-Retardant-Power-Cable-NEK606
Standard	DIN	**Material**	Tinned Copper/EPR insulation/SHF2 Sheath or SHF Mud
Weight / Size	P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable Cable Construction Classification Code Construction details Conductor Tinned Annealed Stranded Copper Wire Insulation R EP Rubber Outer Sheath U Halogen-free Thermoset compound SHF2 Halogen-free mud resistant thermoset compound, SHF Mud Standards Design : IEC 60092-354 NEK 606-2004 IEC 60332-3 Category A IEC60754-1 IEC 61034-1 Cores & Size Cores:	**Certificate**	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable (NEK606):
- Standards
- Feature
- Shipment:
- Cable Construction
- Cores & Size
- Application:

China P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable (NEK606):



P18 RU 0.6/1KV Halogen-free Flame Retardant Power Cable

Cable Construction

Classification	Code	Construction details
Conductor	Tinned Annealed Stranded Copper Wire	
Insulation	R	EP Rubber
Outer Sheath	U	Halogen-free Thermoset compound SHF2
Halogen-free mud resistant thermoset compound, SHF Mud		

Standards

Design : IEC 60092-354

NEK 606-2004

IEC 60332-3 Category A

IEC60754-1

IEC 61034-1

Cores & Size

Cores: 1,2,3

Size (sqmm): 1.5, 2.5, 4, 6,10, 16, 25, 35, 50, 70, 95, 120, 150, 185

Feature

Halogen-free, Low Smoke, Flame retardant, Mud Resistant

Application:

The cable is fixed installation in explosion risk and safe area; High Voltage power cables for general purposes; SHF Mud for Installation in areas expose to Mud and Drilling or Cleaning fluids

Shipment:

We can delivery at everywhere around the world according to Incoterms 2010.