

OTHER MARINE VALVES & ACCESSORIES

PDF27 Single-Circuit Brake Valve

PDF27 Single-Circuit Brake Valve The single-circuit hydraulic brake valve adopts the principle of a direct-acting three-way pressure reducing valve. The brake pressure is proportional to the stroke of the operat...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Other Marine Valves & Accessories
Standard	GB
Weight / Size	Approximate Weight 2.3Kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications


Category	Other Marine Valves & Accessories	Model / SKU	PDF27-Single-Circuit-Brake-Valve
Standard	GB	Weight / Size	Approximate Weight 2.3Kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China PDF27 Single-Circuit Brake Valve:

PDF27 Single-Circuit Brake Valve

The single-circuit hydraulic brake valve adopts the principle of a direct-acting three-way pressure reducing valve. The brake pressure is proportional to the stroke of the operating control element or the stroke angle of the pedal, and the operating force is also proportional to the stroke of the actuator. The foot-operated valve features an ergonomic angle for easy and effortless operation. All pedals are equipped with anti-slip function.

Principle :



Max. Pressure at Port P	20 MPa
Max.Braking Pressure at Port A	12 MPa
Return-line Back Pressure	≤ 0.5 MPa
Viscosity Range	10-380 mm ² /s
Temperature Range	-20 °C ~ 100 °C
Oil Fluid Cleanliness	The solid-particle contamination level of oil fluid and system shall not exceed GB/T 14039-2002-/19/16 or NAS 1638 Class 10.
Approximate Weight	2.3Kg