

FIRE MONITOR

PS100W Fixed Type Fire Monitor

PS100W Fixed Type Fire Monitor Flow rate 80L/S 100L/S Range ≥80 meter ≥85 meter ...

ISO9001 Supplier

Class Certificate

Export Supply

Loading product image...

Key Highlights

Category	Fire Monitor
Material	Stainless steel
Weight / Size	PS100W Fixed Type Fire Monitor Flow rate 80L/S 100L/S Range ≥80 meter ≥8...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Fire Monitor	Model / SKU	PS100W-Fixed-Type-Fire-Monitor
Material	Stainless steel	Weight / Size	PS100W Fixed Type Fire Monitor Flow rate 80L/S 100L/S Range ≥80 meter ≥85 meter Rated working pressure 1.2Mpa Working pressure range 0.8-1.6MPa Material Stainless steel Operating handle Straight shank Hand wheel Connection Flange connection Connection flange size DN100/DN65/DN80 Horizontal rotation 360 degree Pitch angle -60~90
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China PS100W Fixed Type Fire Monitor:

PS100W Fixed Type Fire Monitor



Flow rate	80L/S	100L/S
Range	≥80 meter	≥85 meter
Rated working pressure	1.2Mpa	
Working pressure range	0.8-1.6MPa	
Material	Stainless steel	
Operating handle	Straight shank	Hand wheel
Connection	Flange connection	
Connection flange size	DN100/DN65/DN80	
Horizontal rotation	360 degree	
Pitch angle	-60~90	