


MARINE EXPANSION JOINT

# Packing Type Expansion Joint

The product is suitable to for ship bilge water, ballast water, fresh water, sea water, fire water and oil transfer pipelines, the medium temperature≤170°C. Products standard: CB/T4106-2008 Flange standard: GB2506-89&nb...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

<b>Category</b>	Marine Expansion Joint
<b>Standard</b>	GB
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Marine Expansion Joint	<b>Model / SKU</b>	Packing-Type-Expansion-Joint
<b>Standard</b>	GB	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

**CONTENTS**

- China Packing Type Expansion Joint:
- Packing Type Expansion Joint Main Specifications

## China Packing Type Expansion Joint:

The product is suitable to for ship bilge water, ballast water, fresh water, sea water, fire water and oil transfer pipelines, the medium temperature≤170°C.

Products standard: CB/T4106-2008

Flange standard: GB2506-89

Working pressure: 1.0MPa -1.6MPa



## Packing Type Expansion Joint Main Specifications

Model	DN	A	B	C	D	n	d	Installation length	Working pressure
	mm					mm	mm	MPa	
SHD-65	65	185	145	385	305	4	18	345	1.6
SHD-80	80	200	160	385	305	8	18	345	1.6
SHD-100	100	220	180	385	305	8	18	345	1.6
SHD-125	125	250	210	385	305	8	18	345	1.6
SHD-150	150	285	240	385	305	8	22	345	1.6
SHD-200	200	340	295	400	320	8	22	360	1.0
SHD-250	250	395	350	405	325	12	22	365	1.0
SHD-300	300	445	400	405	325	12	22	365	1.0
SHD-350	350	505	460	410	330	16	22	370	1.0
SHD-400	400	565	515	430	350	16	26	390	1.0
SHD-450	450	615	565	430	350	20	26	390	1.0
SHD-500	500	670	620	440	360	20	26	400	1.0
SHD-600	600	780	725	460	380	20	30	420	1.0
SHD-700	700	895	840	480	400	24	30	440	1.0
SHD-800	800	1015	950	480	400	24	33	440	1.0
SHD-900	900	1115	1050	480	400	26	33	440	1.0