

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## GASOLINE ENGINE DRIVEN WATER PUMP

# Portable gasoline fire pump

Portable gasoline fire pump Parameter Portable gasoline fire pump Set Model 13A-G 20A-G

...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Gasoline engine driven water pump
Standard	EN
Weight / Size	Head lift(m) 65 65 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capa...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Gasoline engine driven water pump	<b>Model / SKU</b>	Portable-gasoline-fire-pump
<b>Standard</b>	EN	<b>Weight / Size</b>	Head lift(m) 65 65 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capacity(m3/h) 45 51 Max.Head lift(m) 75 75 Engine Engine model G390 G620 Cylinder number single double Engine type 4-stroke,air cooled, gasoline engine BorexStroke(mm) 88x75 77x66 Displacement(ml) 397 598 Rated power(kw) 5.7 15 Max.output power(HP) 13 20 Rated spee(RPM) 3000 3000 Mix.Spee(RPM) <1300 <1300 Fuel consumption ratio(g/kw.h) <390 <395 Fuel type 90#,93#,97# Oil type SAE15W-40 starting method Electric start Fuel tank capacity(L) 6 10 Oil capacity(L) 1.1 1.3 Pack Packing size(mm) 810x490x550 850x910x690 Net weight(Kgs) 65 67 Gross weight(Kgs) 80 90
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

**CONTENTS**

- Portable gasoline fire pump

- Parameter

## Portable gasoline fire pump

### Parameter

Portable gasoline fire pump

Set	Model	13A-G	20A-G
	Name	Portable gasoline fire pump	
	Inlet/Outlet diameter	65mm(2.5")	80mm(3")
	Cont. Capacity(m3/h)	37.2	37.2
	Cont. Head lift(m)	65	65
	Suction.Time	20s	20s
	Max.Suction head(m)	8	8
	Max.Capacity(m3/h)	45	51
	Max.Head lift(m)	75	75
Engine	Engine model	G390	G620
	Cylinder number	single	double
	Engine type	4-stroke,air cooled, gasoline engine	
	BorexStroke(mm)	88x75	77x66
	Displacement(ml)	397	598
	Rated power(kw)	5.7	15
	Max.output power(HP)	13	20
	Rated spee(RPM)	3000	3000
	Mix.Spee(RPM)	<1300	<1300
	Fuel consumption ratio(g/kw.h)	<390	<395
	Fuel type	90#,93#,97#	
	Oil type	SAE15W-40	
	starting method	Electric start	
	Fuel tank capacity(L)	6	10
Oil capacity(L)	1.1	1.3	
Pack	Packing size(mm)	810x490x550	850x910x690
	Net weight(Kgs)	65	67
	Gross weight(Kgs)	80	90