GASOLINE ENGINE DRIVEN WATER PUMP

# Portable gasoline fire pump

Portable gasoline fire pump Parameter Portable gasoline fire pump Set Model 13A-G 20A-G ...

ISO9001 Supplier

Class Certificate

Export Supply




## Key Highlights

| | |
|---|---|
| **Category** | Gasoline engine driven water pump |
| **Standard** | EN |
| **Weight / Size** | Head lift(m) 65 65 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capa... |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications | | | |
|---|---|---|---|
| **Category** | Gasoline engine driven water pump | **Model / SKU** | Portable-gasoline-fire-pump |
| **Standard** | EN | **Weight / Size** | Head lift(m) 65 65 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capacity(m3/h) 45 51 Max.Head lift(m) 75 75 Engine Engine model G390 G620 Cylinder number single double Engine type 4-stroke,air cooled, gasoline engine BorexStroke(mm) 88x75 77x66 Displacement(ml) 397 598 Rated power(kw) 5.7 15 Max.output power(HP) 13 20 Rated spee(RPM) 3000 3000 Mix.Spee(RPM) <1300 <1300 Fuel consumption ratio(g/kw.h) <390 <395 Fuel type 90#,93#,97# Oil type SAE15W-40 starting method Electric start Fuel tank capacity(L) 6 10 Oil capacity(L) 1.1 1.3 Pack Packing size(mm) 810x490x550 850x910x690 Net weight(Kgs) 65 67 Gross weight(Kgs) 80 90 |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | **Warranty** | 12 Months unless specified otherwise |
| **Origin** | China | | |

**CONTENTS**


- Portable gasoline fire pump
- Parameter


## Portable gasoline fire pump

## Parameter

Portable gasoline fire pump

| | | | |
|---|---|---|---|
| Set | Model | 13A-G | 20A-G |
| | Name | Portable gosoline fire pump | |
| | Inlet/Outlet diameter | 65mm(2.5") | 80mm(3") |
| | Cont. Capacity(m3/h) | 37.2 | 37.2 |
| | Cont. Head lift(m) | 65 | 65 |
| | Suction.Time | 20s | 20s |
| | Max.Suction head(m) | 8 | 8 |
| | Max.Capacity(m3/h) | 45 | 51 |
| | Max.Head lift(m) | 75 | 75 |
| Engine | Engine model | G390 | G620 |
| | Cylinder number | single | double |
| | Engine type | 4-stroke,air cooled, gasoline engine | |
| | BorexStroke(mm) | 88x75 | 77x66 |
| | Displacement(ml) | 397 | 598 |
| | Rated power(kw) | 5.7 | 15 |
| | Max.output power(HP) | 13 | 20 |
| | Rated spee(RPM) | 3000 | 3000 |
| | Mix.Spee(RPM) | <1300 | <1300 |
| | Fuel consumption ratio(g/kw.h) | <390 | <395 |
| | Fuel type | 90#,93#,97# | |
| | Oil type | SAE15W-40 | |
| | starting method | Electric start | |
| | Fuel tank capacity(L) | 6 | 10 |
| | Oil capacity(L) | 1.1 | 1.3 |
| Pack | Packing size(mm) | 810x490x550 | 850x910x690 |
| | Net weight(Kgs) | 65 | 67 |
| | Gross weight(Kgs) | 80 | 90 |