

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## LIFEBOAT AND RESCUE BOAT ACCESSORIES

# QJ6158 Marine DC regulated power supply

ISO9001 Supplier

Class Certificate

Export Supply

QJ6158 Marine DC regulated power supply &nbsp;&nbsp;&nbsp;Model QJ6158  
&nbsp;&nbsp;&nbsp;Input&nbsp;voltage AC110/220V ...



### Key Highlights

<b>Category</b>	Lifeboat And Rescue Boat Accessories
<b>Standard</b>	EN
<b>Weight / Size</b>	QJ6158 Marine DC regulated power supply Model QJ6158 Input voltage A...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Lifeboat And Rescue Boat Accessories	<b>Model / SKU</b>	QJ6158-Marine-DC-regulated-power-supply
<b>Standard</b>	EN	<b>Weight / Size</b>	QJ6158 Marine DC regulated power supply Model QJ6158 Input voltage AC110/220V Maximum float voltage DC28.5V±0.5V Maximum limiting current 30A Ripple&Noise ≤30mV Low battery alarm 21V-22V Automatically begin charging voltage 23V-24V Automatically stop charging voltage 28.5V-29V Weight 23kg Dimensions(WxHxD) 322x200x402mm Applicable scope GMDSS
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

## QJ6158 Marine DC regulated power supply

Model	QJ6158
Input voltage	AC110/220V
Maximum float voltage	DC28.5V±0.5V
Maximum limiting current	30A
Ripple&Noise	≤30mV
Low battery alarm	21V-22V
Automatically begin charging voltage	23V-24V
Automatically stop charging voltage	28.5V-29V
Weight	23kg
Dimensions(WxHxD)	322x200x402mm
Applicable scope	GMDSS