

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

CHAIN SLING

RA Round Sling

Description RA round sling is soft in texture and with multiple suspension points and is entanglement. Suitable for all kinds of complicated situations of hoisting. Technical Data ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chain Sling
Standard	EN
Weight / Size	Technical Data Products code Working load limit (kg) Approximate thicknes...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications

Category	Chain Sling	Model / SKU	RA-Round-Sling
Standard	EN	Weight / Size	Technical Data Products code Working load limit (kg) Approximate thickness (mm) Approximate width (mm) Min length (m) Max length(m) RA1/2 500 4 50 0.50 RA001 1000 6 50 0.50 RA002 2000 8 60 0.50 RA003 3000 9 70 0.50 RA004 4000 11 70 0.50 RA005 5000 13 85 0.50 RA006 6000 13 85 1.00 RA008 8000 13 120 1.00 RA010 10000 14 120 2.00 RA012 12000 15 130 2.00 RA015 15000 18 130 2.00 RA020 20000 20 140 2.50 RA025 25000 24 140 2.50 To be customized RA030 30000 32 145 2.50 RA040 40000 40 150 2.50 RA050 50000 45 175 2.50 RA060 60000 65 205 4.00 RA080 80000 70 250 4.00 RA100 100000 80 290 4.00 RA200 200000 120 465 5.00 RA300 300000 160 555 5.00 RA400 400000 200 700 5.00 RA500 500000 220 790 8.00 RA600 600000 240 875 8.00 RA700 700000 260 920 8.00 RA800 800000 280 985 8.00 RA900 900000 300 1050 9.00 RA1000 1000000 320 1080 9.00
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ Description ■ Technical Data
-----------------	---

Description

RA round sling is soft in texture and with multiple suspension points and is entanglement. Suitable for all kinds of complicated situations of hoisting.

Technical Data





Products code	Working load limit (kg)	Approximate thickness (mm)	Approximate width (mm)	Min length (m)	Max length(m)	
RA1/2	500	4	50	0.50		
RA001	1000	6	50	0.50		
RA002	2000	8	60	0.50		
RA003	3000	9	70	0.50		
RA004	4000	11	70	0.50		
RA005	5000	13	85	0.50		
RA006	6000	13	85	1.00		
RA008	8000	13	120	1.00		
RA010	10000	14	120	2.00		
RA012	12000	15	130	2.00		
RA015	15000	18	130	2.00		
RA020	20000	20	140	2.50		
RA025	25000	24	140	2.50		To be customized
RA030	30000	32	145	2.50		
RA040	40000	40	150	2.50		
RA050	50000	45	175	2.50		
RA060	60000	65	205	4.00		
RA080	80000	70	250	4.00		
RA100	100000	80	290	4.00		
RA200	200000	120	465	5.00		
RA300	300000	160	555	5.00		
RA400	400000	200	700	5.00		
RA500	500000	220	790	8.00		
RA600	600000	240	875	8.00		
RA700	700000	260	920	8.00		

RA800	800000	280	985	8.00
RA900	900000	300	1050	9.00
RA1000	1000000	320	1080	9.00