

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## HIGH PRESSURE PUMP

# RG100-L-G High pressure hose Distributor Adapter

ISO9001 Supplier

Class Certificate

Export Supply

Model Max working pressure (MPa) Minimum burst pressure (MPa) Inner diameter x outer diameter (mm) Minimum bending radius (mm) ...



### Key Highlights

Category	High Pressure Pump
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.


### Technical Specifications

Category	High Pressure Pump	Model / SKU	RG100-L-G-High-pressure-hose-Distributor-Adapter
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

#### CONTENTS

- China RG100-L-G High pressure hose Distributor Adapter:
- Adapter
- Distributor

### China RG100-L-G High pressure hose Distributor Adapter:

Model	Max working pressure (MPa)	Minimum burst pressure (MPa)	Inner diameter x outer diameter (mm)	Minimum bending radius (mm)	Temperature
					 0.085075s

RG70-L-G	70	186	6.3x12.4	70	-40°C-+100°C
RG100-L-G	100	320	6.3x13.3	80	-40°C-+100°C
RG180-L-G	180	450	4.7x11.5	130	-40°C-+100°C
RG250-L-G	250	625	4.7x13.0	175	-40°C-+100°C

Note: L represents the required length in millimeters, and G represents the thread of the hose joint.

Example: RG180-1000-G1/4, which refers to a hose with a length of 1000mm, a G1/4 external thread hose connector, and a maximum pressure resistance of 180Mpa.

## Distributor

分配器 Distributor



三通分配器  
Three pass distributor

五通分配器  
Five pass distributor

九通分配器  
Nine pass distributor

## Adapter

规格型号	示意图	接口1	接口2	工作压力	产品备注
G1/EP-G1/EP		G1/EP	G1/EP	300 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: G1/4 外螺纹 120 度外锥面
G1/EP-3/8-180°NC		G1/EP	3/8-180°NC	300 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: 3/8-180°P 外螺纹 40 度内锥面
G1/EP-3/4-180°NC		G1/EP	3/4-180°NC	300 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: 3/4-180°P 外螺纹 40 度内锥面
G1/EP-W6.6L.5C		G1/EP	W6.6L.5C	300 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: W6.6L.5 外螺纹 40 度外锥面
G1/EP-W23.1L.5C		G1/EP	W23.1L.5C	300 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: W23.1L.5 外螺纹 40 度外锥面
G1/EP-NPT1/8		G1/EP	NPT1/8	150 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: NPT1/8 外螺纹
G1/EP-3/8-180°NC		G1/EP	3/8-180°NC	250 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: 3/8-180°P 外螺纹 40 度内锥面
G1/EP-W14.1L.5C		G1/EP	W14.1L.5C	250 MPa	螺纹1: G1/4 外螺纹 120 度外锥面 螺纹2: W14.1L.5 外螺纹 40 度内锥面
G1/EP 堵头		G1/EP	—	300 MPa	螺纹1: G1/4 外螺纹 120 度外锥面堵头
G1/EC-G1/EP		G1/EC	G1/EP	250 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: G1/4 外螺纹 120 度外锥面
G1/EP-3/8-180°NC		G1/EP	3/8-180°NC	250 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: 3/8-180°P 外螺纹 40 度外锥面
G1/EP-3/4-180°NC		G1/EP	3/4-180°NC	250 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: 3/4-180°P 外螺纹 40 度外锥面
G1/EC-W6.6L.5C		G1/EC	W6.6L.5C	250 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: W6.6L.5 外螺纹 40 度外锥面
G1/EC-W23.1L.5C		G1/EC	W23.1L.5C	250 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: W23.1L.5 外螺纹 40 度外锥面
G1/EC-NPT1/4		G1/EC	NPT1/4	150 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: NPT1/4 外螺纹
G1/EC-NPT3/8		G1/EC	NPT3/8	150 MPa	螺纹1: G1/4 外螺纹 40 度内锥面 螺纹2: NPT3/8 外螺纹