

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## ELECTRIC HEATER

# RGT-60L Marine Titling Boiling Pan

Marine Titling Boiling Pan Product introduction : 1. The shell adopts 304 stainless steel material, elegant appearance, easy cleaning, easy cleaning, durable; 2. The core components (such as elec...

ISO9001 Supplier

Class Certificate

Export Supply



## Key Highlights

Category	Electric Heater
Standard	EN
Material	Stainless steel 304
Weight / Size	Model Dimension(mm) Capacity(L) Power (kw) Volts(v) HZ N/W(kg) RGT-60L 7...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

Category	Electric Heater	Model / SKU	RGT-60L-Marine-Titling-Boiling-Pan
Standard	EN	Material	Stainless steel 304
Weight / Size	Model Dimension(mm) Capacity(L) Power (kw) Volts(v) HZ N/W(kg) RGT-60L 700X700X850 60L 9 380v/415v/440v/480v-3p 50/60Hz 88 RGT-100L 800X900X850 100L 12 380v/415v/440v/480v-3p 50/60Hz 123 RGT-150L 800X900X850 150L 15 380v/415v/440v/480v-3p 50/60Hz 130	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China



0.056242s

**CONTENTS**

■ Marine Titling Boiling Pan

■ Product introduction :

■ Technical data:

**Marine Titling Boiling Pan****Product introduction :**

1. The shell adopts 304 stainless steel material, elegant appearance, easy cleaning, easy cleaning, durable;
2. The core components (such as electric heating tube, temperature controller etc.) imported from Germany, the greatest degree of protection of stable and reliable performance;
3. The big power, fast heating, high heating, safe and reliable, anti dry burning;
4. The water inlet and outlet convenient;
5. The automatic temperature setting, temperature control range 30~100°C adjustable;
6. The adjustable foot, adjustable range of positive and negative 30mm.

**Technical data:**

Model	Dimension(mm)	Capacity(L)	Power (kw)	Volts(v)	HZ	N/W(kg)
RGT-60L	700X700X850	60L	9	380v/415v/440v/480v-3p	50/60Hz	88
RGT-100L	800X900X850	100L	12	380v/415v/440v/480v-3p	50/60Hz	123
RGT-150L	800X900X850	150L	15	380v/415v/440v/480v-3p	50/60Hz	130