

CHAIN SLING

RH02 High Tensile Eye Type Sling

Description: It is made of Ultra High Molecular Weight Polyethylene fiber, the tensile of which is 3-4 times of polyester fiber. It is High modulus and low elongation type fiber and the ...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights	
Category	Chain Sling
Standard	EN
Material	Cotton, nylon, synthetic fiber, polyester fiber
Weight / Size	It is made of Ultra High Molecular Weight Polyethylene fiber, the tensil...
Certificate	CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Chain Sling	Model / SKU	RH02-High-Tensile-Eye-Type-Sling
Standard	EN	Material	Cotton, nylon, synthetic fiber, polyester fiber
Weight / Size	It is made of Ultra High Molecular Weight Polyethylene fiber, the tensile of which is 3-4 times of polyester fiber.	Certificate	CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> ■ Description: 	<ul style="list-style-type: none"> ■ Technical data:
-----------------	--	---

Description:



- It is made of Ultra High Molecular Weight Polyethylene fiber, the tensile of which is 3-4 times of polyester fiber. It is High modulus and low elongation type fiber and the proportion is 0.97g/cm³(lighter than water).
- The performance of the fiber such as UV-resistant, shock - resistant, acid - resistant, corrosion - resistant, wear – resistant, etc. are all much better than other synthetic fibers.
- Advantages: Small size, light weight, soft, safe, low elongation rate, UV-resistant, wear – resistant, shock - resistant, corrosion – resistant, non-conductive, anti-static, long service life.
- Low-temperature performance is good, operating temperature range: -125°C~80°C, the weight is 1/4 of common round sling and the diameter is 1/2 of common round sling.

Technical data:



Art.No.	Working Load Limit (kg)	Approx Thickness (mm)	Approx Width (mm)	Minimum length L(m)
RRH02-01	1000	12	24	1.5
RH02-02	2000	18	26	1.5
RH02-03	3000	22	35	1.5
RH02-04	4000	25	45	1.5
RH02-05	5000	30	50	1.5
RH02-06	6000	32	55	2
RH02-08	8000	35	65	2
RH02-10	10000	38	70	3
RH02-12	12000	40	75	3
RH02-15	15000	45	80	4
RH02-20	20000	45	95	4
RH02-25	25000	48	110	4
RH02-30	30000	60	125	6

RH02-40	40000	65	130	6
RH02-50	50000	70	140	8
RH02-60	60000	72	150	8
RH02-80	80000	75	155	10
RH02-100	100000	80	160	15

