

CHAIN SLING

RK01 Fireproof Endless Type Sling

Description: It uses a high-strength, high-temperature resistant aramid fiber to make a round sling with flame retardant fire resistance. The sling is light, soft, flame retardant, high temperature resistant, ex...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chain Sling
Standard	DIN
Weight / Size	It has an ambient temperature range of -40 ° C to 180 ° C and a weight o...
Certificate	CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Chain Sling	Model / SKU	RK01-Fireproof-Endless-Type-Sling
Standard	DIN	Weight / Size	It has an ambient temperature range of -40 ° C to 180 ° C and a weight of 1/2 of the ordinary sling.
Certificate	CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Description:

■ Technical data:

Description:

It uses a high-strength, high-temperature resistant aramid fiber to make a round sling with flame retardant fire resistance.

The sling is light, soft, flame retardant, high temperature resistant, excellent wear resistance, high strength, low elongation, large safety factor, long service life, non-conductivity, no electric shock hazard, and good resistance to

chemical corrosion. Strength and other advantages.
It is suitable for use in fireworks and high temperature environments. It has an ambient temperature range of -40 ° C to 180 ° C and a weight of 1/2 of the ordinary sling.



Technical data:

Art.No.	Working Load Limit (kg)	Approx Thickness (mm)	Approx Width (mm)	Minimum length L(m)
RK01-01	1000	4	30	1
RK01-02	2000	5	40	1
RK01-03	3000	6	50	1.5
RK01-04	4000	7	60	1.5
RK01-05	5000	8	70	1.5
RK01-06	6000	9	75	2
RK01-08	8000	11	80	2
RK01-10	10000	13	90	2
RK01-12	12000	14	100	3
RK01-15	15000	16	110	3
RK01-20	20000	18	125	3