

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## HIGH PRESSURE PUMP

# RMC Series Volume Synchronous Jacking System-Economical

- ISO9001 Supplier
- Class Certificate
- Export Supply

RMC Series Volume Synchronous Jacking System-Economical &nbsp; System features: Double plunger pump power system is adopted to achieve rapid leveling and heavy load leveling. The control precision is high, the synchr...



### Key Highlights

Category	High Pressure Pump
Standard	DIN
Weight / Size	Sync Points Model Nominal Pressure Nominal Capcaity Oil Tank 380...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	High Pressure Pump	<b>Model / SKU</b>	RMC-Series-Volume-Synchronous-Jacking-System-Economical
<b>Standard</b>	DIN	<b>Weight / Size</b>	Sync Points Model Nominal Pressure Nominal Capcaity Oil Tank 380v,50Hz) Weight Mpa L/min L Kg 2 PMCDO2D 70 0.5x2 100 1.5KW 125 2 PMCDO2S 70 0.5x2 100 1.5KW 125 4 PMCDO4D 70 0.5x4 100 2.2KW 125 4 PMCDO4S 70 0.5x4 100 2.2KW 125 8 PMCDO8D 70 0.5x8 100 5.5KW 125 8 PMCDO8S 70 0.5x8 100 5.5KW 125 12 PMCD12D 70 0.5x12 100 11KW 150 12 PMCD12S 70 0.5x12 100 11KW 150 Rated flow can be customized according to customer needs Tank volume can also be customised accroding to customer needs.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

## China RMC Series Volume Synchronous Jacking System-Economical:

RMC Series Volume Synchronous Jacking System-Economical

System features:

Double plunger pump power system is adopted to achieve rapid leveling and heavy load leveling.

The control precision is high, the synchronous precision can reach 0.5mm, and the synchronous jacking and descending can be completely controlled.

The product is flexible and can be controlled flexibly according to different working conditions,oil cylinder tonnage and quantity and jacking accuracy.

Each control point is relatively independent and can be adjusted independently to one or several control points without interference between the control points.

The system adopts modular design, which can control 4,8,12,16 ,and can be extended to 99 points online.

According to the working condition,the access displacement sensor and pressure sensor can be selected to monitor the system working condition in real time.

Sync Points	Model	Nominal Pressure	Nominal Capcaity	Oil Tank	380v,50Hz)	Weight
		Mpa	L/min	L		Kg

2	PMCDO2 D	70	0.5x2	100	1.5KW	125
2	PMCDO2 S	70	0.5x2	100	1.5KW	125
4	PMCDO4 D	70	0.5x4	100	2.2KW	125
4	PMCDO4 S	70	0.5x4	100	2.2KW	125
8	PMCDO8 D	70	0.5x8	100	5.5KW	125
8	PMCDO8 S	70	0.5x8	100	5.5KW	125
12	PMCD12 D	70	0.5x12	100	11KW	150
12	PMCD12 S	70	0.5x12	100	11KW	150

Rated flow can be customized according to customer needs

Tank volume can also be customised according to customer needs.

Motor can be selected according to the requirements of variable speed motor( VFDM)