GRAB BUCKETS

Remote Control Grab

ISO9001 Supplier

Class Certificate

Export Supply

Remote Control Grab Remote control grab is an efficient tool for lodaing and unloding bulk cargo. The grab closes by lifting crane and opens by transmitter without any additional power. The hydraulic and electric ...



Key Highlights

Category	Grab Buckets
Standard	DIN
Weight / Size	Grab opening speed can be adjusted by cargo weight, so grab opening will...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Grab Buckets	**Model / SKU**	Remote-Control-Grab
Standard	DIN	**Weight / Size**	Grab opening speed can be adjusted by cargo weight, so grab opening will not has inpact to crane and can ensure grab opening with high speed.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Remote Control Grab
- Specification

Remote Control Grab

Remote control grab is an efficient tool for lodaing and unloding bulk cargo. The grab closes by lifting crane and opens by transmitter without any additional power. The hydraulic and electric parts are plug-in modular design, easily maintain and repair, suitable for ship ocean voyages. The electric system and hydraulic system is water proof design, which can

prevent the grab from wave and rain washing. Each grab is tested strictly by immersed under water 24hours. Grab opening speed can be adjusted by cargo weight, so grab opening will not has inpact to crane and can ensure grab opening with high speed. Grab can work for long time with low trouble rate. Fully charged battery can work more than 180 hour. Easy operation, crane does not need any other auxiliary equipment. Grab can work immediately when put on crane hook. Remote control grabs are now widely used on bulk vessels, ports, and are exported in baches.

Specification

Model	capacity(m3)	Total lifting weight(t)	Dead weight(t)	dimension(mm)						
				A	B	c	D	E	Pulley diameter(mm)	Wire rope diameter(mm)
YK10[3-6]4.5	3-6	10	4.5	26000	33338	37556	40771	27000	445	24
YK14(4-7]6	4-7	14	6	27800	33398	40922	44448	28000	520	28
YK16(4-8]7	4-8	16	7	27800	33398	40922	44448	30000	520	28
YK20[5-10]8	5-10	20	8	28100	35591	41922	45133	35600	560	32
YK25(6-12]10	6-12	25	10	30000	38387	44887	48500	41000	650	36
YK28[8-16]10.5	8-16	28	10.5	30060	38887	45559	48881	43200	650	36
YK32(10- 20] 13.5	10-20	35	14	32700	41099	50088	53911	46000	720	40
YK40(12-24]17	12-24	40	17	35200	43744	51366	54955	47000	800	45
YK50(15-30]21	15-30	50	21	40000	48873	58500	60722	49000	880	52