TURNBUCKLE

Rigging Screw With Eye And Jaw

Main Specification Turnbuckle usually Forged, Free forged and Casting. The surface of turnbuckle original color, galvanised,hot galvanized Material is 45# Steel, Q235 Size Table ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Turnbuckle
Material	45# Steel, Q235
Weight / Size	The surface of turnbuckle original color, galvanised,hot galvanized Mate...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Turnbuckle	**Model / SKU**	Rigging-Screw-With-Eye-And-Jaw
Material	45# Steel, Q235	**Weight / Size**	The surface of turnbuckle original color, galvanised,hot galvanized Material is 45# Steel, Q235 Size Table SWL A B C D1 D2 D3 D4 E1 E2 E3 Weight kgs .Tons mm mm mm mm mm mm mm mm mm mm kg 0.1 6 102 12 3 5 15 7 6 15 8 0.11 0.15 88 110 15 4 6 16 9 7 19 10 0.23 0.375 10 152 21 5 8 21 11 8 25 11 0.28 0.5 12 175 27 6 10 25 13 11 30 14 0.8 0.75 16 229 27 10 12 40 18 14 41 16 1.4 1.125 20 229 33 12 16 45 20 16 51 22 2 1.6 22 305 33 15 18 48 24 16 51 22 3.5 2 24 325 42 16 22 65 28 19 57 25 4 2.75 28 356 48 18 22 59 30 19 57 28 4.5 3.75 33 381 48 20 27 62 34 22 65 35 6.5 4.25 35 381 60 22 28 68 38 22 65 36 8 5 39 406 60 24 33 74 42 25 74 38 11
Surface	galvanized	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- Main Specification
- Size Table


Main Specification

Turnbuckle usually Forged, Free forged and Casting.

The surface of turnbuckle original color, galvanised,hot galvanized

Material is 45# Steel, Q235

Size Table



SWL	A	B	C	D1	D2	D3	D4	E1	E2	E3	Weight kgs
.Tons	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
0.1	6	102	12	3	5	15	7	6	15	8	0.11
0.15	88	110	15	4	6	16	9	7	19	10	0.23
0.375	10	152	21	5	8	21	11	8	25	11	0.28
0.5	12	175	27	6	10	25	13	11	30	14	0.8
0.75	16	229	27	10	12	40	18	14	41	16	1.4
1.125	20	229	33	12	16	45	20	16	51	22	2
1.6	22	305	33	15	18	48	24	16	51	22	3.5
2	24	325	42	16	22	65	28	19	57	25	4
2.75	28	356	48	18	22	59	30	19	57	28	4.5
3.75	33	381	48	20	27	62	34	22	65	35	6.5
4.25	35	381	60	22	28	68	38	22	65	36	8
5	39	406	60	24	33	74	42	25	74	38	11