

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

NEK606 CABLE

S2 RFOU(c) 250V Halogen-free Flame Retardant Communication Cable NEK606

ISO9001 Supplier

Class Certificate

Export Supply

S2 RFOU(c) 250V Halogen-free Flame retardant Instrumentation & Communication Cable with Collective screened S2/S6 RFOU(c) 250V Halogen-free Mud Resistant Flame retardant Instrumentation & Communication Cabl...



Key Highlights

Category	NEK606 Cable
Standard	DIN
Material	Tinned Copper/EP Rubber/Twisted+Collective Screened/SHF2 Sheath/Tinned C...
Weight / Size	IEC 60092-376 NEK 606-2004 IEC 60332-3 Flame Retardant Category A IEC607...
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	NEK606 Cable	Model / SKU	S2-RFOU-c-250V-Halogen-free-Flame-Retardant-Communication-Cable-NEK606
Standard	DIN	Material	Tinned Copper/EP Rubber/Twisted+Collective Screened/SHF2 Sheath/Tinned Copper Wire Braided/ SHF2 Sheath or SHF Mud
Weight / Size	IEC 60092-376 NEK 606-2004 IEC 60332-3 Flame Retardant Category A IEC60754-1 Halogen-free IEC 61034-1 Low Smoke Cores & Size Cores:	Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China S2 RFOU(c) 250V Halogen-free Flame Retardant Communication Cable NEK606:	■ Cable Construction
	■ Standards	■ Cores & Size
	■ Feature	■ Application:

China S2 RFOU(c) 250V Halogen-free Flame Retardant Communication Cable NEK606:



S2 RFOU(c) 250V Halogen-free Flame retardant Instrumentation & Communication Cable with Collective screened
 S2/S6 RFOU(c) 250V Halogen-free Mud Resistant Flame retardant Instrumentation & Communication Cable with Collective screened

Cable Construction

Classification	Code	Construction details
Conductor	Tinned Annealed Stranded Copper Wire	
Insulation	R	EP Rubber
Twisting	Color coded cores twisted together for pair or triple	
Individual Screen	(c)	Both Pair/Triple are collective screened by aluminum polyester with copper wire
Bedding/Inner Covering	F	Halogen-free compound SHF1
Aarmor	O	Tinned Copper wire braided
Outer Sheath	U	Halogen-free Thermoset compound SHF2
Halogen-free mud resistant thermoset compound, SHF Mud		
Colour	Grey or Blue	

Standards

Design : IEC 60092-376

NEK 606-2004

IEC 60332-3 Flame Retardant Category A

IEC60754-1 Halogen-free

IEC 61034-1 Low Smoke

Cores & Size

Cores: 1P 2P 3P 4P 7P 8P 10P 12P 14P 16P 18P 19P 24P 32P

1T 2T 3T 4T 7T 8T 10T 12T 14T 16T 18T 19T 24T 32T

Size (sqmm): 0.75 1 1.5

Feature

Halogen-free, Low Smoke, Flame retardant, Mud Resistant

Application:

The cable is fixed installation for Instrumentation, Communication, Control and Alarm system in both explosion risk and safe area; SHF Mud for Installation in areas expose to Mud and Drilling or Cleaning fluids

