

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## HIGH PRESSURE PUMP

## SPJ Marine manual injector calibration pump

ISO9001 Supplier

Class Certificate

Export Supply

SPJ manual injector calibration pump: SPJ injector calibration pump has the advantages of durability, good sealing, large calibration pressure range, accurate pressure adjustment value, reasonable structure, novel ...



### Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	Pressure range 0-60MPa Oil pump displacement 2.8ml / stroke Oil cup capa...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	High Pressure Pump	Model / SKU	SPJ-Marine-manual-injector-calibration-pump
Standard	EN	Weight / Size	Pressure range 0-60MPa Oil pump displacement 2.8ml / stroke Oil cup capacity 660ml Overall dimensions 300×150×500 Weight 14kg
Surface	Check the sealing seat surface of fuel injection nozzle coupling.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

#### CONTENTS

- SPJ manual injector calibration pump:
  - Purpose:
  - Specification:



## SPJ manual injector calibration pump:

SPJ injector calibration pump has the advantages of durability, good sealing, large calibration pressure range, accurate pressure adjustment value, reasonable structure, novel shape, convenient and reliable use. It is an updated product of manual injector calibration pump. It is an ideal special calibration tool for diesel engine injectors used in ships, locomotives, diesel engines and other generator sets, laboratories, agricultural machinery stations and transport vehicles. It is suitable for the calibration of various diesel engine injectors with cylinder diameter less than 200mm.

### Purpose:

1. check the spray quality and oil bunches.
2. Check the sealing seat surface of fuel injection nozzle coupling.
3. Adjust the valve opening pressure.

### Specification:

Pressure range	0-60MPa
Oil pump displacement	2.8ml / stroke
Oil cup capacity	660ml
Overall dimensions	300×150×500
Weight	14kg